

	<a href="#">RELAY MODULE UPK-1 EWIMAR</a>	<a href="#">UPS AT-UPS2000RT-RACK 2000 VA EAST</a>	<a href="#">FINAL SOCKET DASFRJ45.01/11-SIMON54 F + RJ45 TYPE</a>
			
	4.75 CHF 4.75 CHF	718.68 CHF 718.68 CHF	15.51 CHF 15.51 CHF
Number of relay outputs	1	...	...
Power adapter type	...	Online	...
Mount	...	...	Flush-mounted, Claw or screw mounting
Power supply	12 V AC/DC	...	...
Nominal power	...	1800 W	...
Apparent Power	...	2000 VA	...
Current consumption	25 mA @ 12 V DC	...	...
Sockets type	...	...	<ul style="list-style-type: none"> <li>• 1 pcs F socket</li> <li>• 1 pcs RJ-45 - UTP cat. 6</li> </ul>
Input voltage	...	230 V AC $\pm$ 25 %	...
Connector	...	...	<ul style="list-style-type: none"> <li>• F socket</li> <li>• KRONE quick-connector</li> </ul>
Relay maximal load	1 A @ 30 V AC/DC (max)	...	...
Input frequency	...	50 / 60 Hz (auto detection)	...
Output	1 x NO/NC	...	...
Output voltage	...	230 V AC $\pm$ 5 % (Pure Sine Wave)	...
Frequency range	...	...	0 ... 2400 MHz - F socket
Connection loss	...	...	1 dB - F socket
Output frequency	...	50 / 60 Hz $\pm$ 1 %	...
Operation temp	-10 °C ... 50 °C	...	...
Voltage adjustment	...	$\pm$ 1 %	...
Application	...	...	Simon 54 product series, for Nature, Premium frames
Frequency adjustment	...	—	...
Transfer time	...	0 ms	...
Color	...	...	White (RAL 9003)
Charging time (recover to 90% capacity)	...	8 hours	...
Battery	...	4 x 12V/9Ah	...
Number of outputs	...	2 pcs CEE 7/3 (Schuko)	...
Management software	...	UPSmart (Windows 95/98/2000/XP/Vista/7/8/10, Linux)	...

Protections	...	<ul style="list-style-type: none"> <li>• Fuse</li> <li>• Overvoltage</li> <li>• Overload protection</li> <li>• EPO (Emergency power off) switch</li> <li>• Ethernet filter</li> </ul>	...
Operation state indication	...	<ul style="list-style-type: none"> <li>• LCD display: operation mode, battery charging level, in/out voltage level, overload indicator,</li> <li>• Sound signaling</li> </ul>	...
Main features	<ul style="list-style-type: none"> <li>• LED indication</li> <li>• 5/20mm delayed fuse - 2 A</li> </ul>	<ul style="list-style-type: none"> <li>• Auto restart while AC is recovering</li> <li>• Automatic Voltage Regulator (AVR)</li> <li>• "Cold Start" function</li> <li>• Compatible with power generators</li> <li>• Remote management - UPSmart application included</li> <li>• Built-in EMI, RFI filter</li> <li>• Excellent microprocessor control guarantees high reliability</li> <li>• UPS auto diagnostic system</li> <li>• Battery charge and maintenance control</li> <li>• USB/RS-232 communication port</li> </ul>	RJ-45 dust cover
Application	...	<ul style="list-style-type: none"> <li>• Surveillance Systems</li> <li>• data storage centers</li> <li>• network, servers, workstations</li> <li>• Industrial Equipment</li> </ul>	...
Housing type	...	Rack/Tower 2-in-1 Design	...
Operation temp. / Relative humidity	...	0 °C ... 40 °C / 0 ~ 90 % (non-condensing)	...
Weight	0.019 kg	22 kg	0.048 kg
Dimensions	40 x 34 x 19 mm	440 x 88 x 658 mm ; RACK 19", 2U	<ul style="list-style-type: none"> <li>• 75 x 75 x 43 mm</li> <li>• 23 mm - mounting depth</li> </ul>
Manufacturer / Brand	EWIMAR	EAST	KONTAKT Simon
Guarantee	2 years	2 years	6 years