




	ACCESS CONTROLLER ASI1212F DAHUA	EXTENDER HDMI-EX-6IR	WALL MOUNTING KIT USP-U30 FOR SOLAR PANELS
			
	229.00 EUR 229.00 EUR	54.34 EUR 54.34 EUR	23.96 EUR 23.96 EUR
Cards support	13.56 MHz S50
Material	Aluminum
Reading distance of prox-keys	1 ... 3 cm
Keyboard built-in	—
Tilt angle adjustment:	15 ° ... 50 °
Autonomous operation	✓
Battery backup support	—
Input lines	3
Output lines	3
Supported HDMI resolutions	...	1080i - 50/60 Hz, 720p, 576p, 576i, 480p, 480i	...
Identification time	< 1.5 s
Maximal transmission range	...	• 45 m @ 720p / 1080i - UTP cat. 5 • 60 m @ 720p / 1080i - UTP cat. 6	...
Communication	• RS-485 • Wiegand • LAN
RS-485 interface	✓
RS-232 interface	—
Wiegand interface	✓
Network interface	10/100 Base-T
Default IP address	192.168.1.108
Supported audio formats	...	DTS-HD, Dolby true HD, LPCM7.1, AC3, DTS, DSD	...
Default admin user / password	admin / - The administrator password should be set at the first start
USB	—
Memory card slot	—
Internal memory	Support storage of 150 000 records

Power supply	12 V DC / 1 A	5 V DC / 1000 mA - 2 pcs of power adapters included	...
Main features	<ul style="list-style-type: none"> • Built-in LCD display 240 x 320 px - 2.8 " capacitive touch screen • Fingerprint reader built-in • Memory of 3000 fingerprint patterns • Possible connection of the external ASR series reader (read in/out door control) • Identification modes : Proximity identifier 13.56 MHz S50, Fingerprint, PIN, Any combination of the above • Remote access verification • Tamper detection - removing from mounting surface • Support for door contact and exit button • Indication of forced entry and the lack of closing doors • 30000 indexed users • Possibility to configure access groups • 128 General Purpose Schedules • 128 time periods within single Schedule • Holiday Schedules • Anti-passback • Integration with an alarm system via in/out line • Remote programming from PC 	IR receiver : 20 ... 60 kHz	Maximum power of the mounted panel : 80 W
"Index of Protection"	—
Operation temp	-10 °C ... 45 °C	-10 °C ... 55 °C	...
Permissible relative humidity	5 ... 90 % (non-condensing)	5 % ... 90 %	...
Dimensions	115 x 115 x 32 mm	72 x 67 x 25 mm	310 x 300 x 43 mm - each item
Weight	0.22 kg	0.08 kg	0.94 kg (total)
Supported languages	English
Manufacturer / Brand	DAHUA
Guarantee	3 years	2 years	2 years