




	<a href="#">CABLE FOR SOLAR INSTALLATIONS H1Z2Z2-K-1X4.0/BK</a>	<a href="#">SET OF UTP / COAXIAL CONVERTERS FOR LAN+POE TRANSMISSION XCOAX4-SET 2 PCS SET ATTE</a>	<a href="#">4-CHANNEL REMOTE CONTROL PL22 VIDOS</a>
			
	0.91 EUR 0.91 EUR	112.62 EUR 112.62 EUR	7.20 EUR 7.20 EUR
Connectors	...	<ul style="list-style-type: none"> <li>• 1 pcs RJ45</li> <li>• 1 pcs cable terminal</li> <li>• 1 pcs BNC</li> </ul>	...
Frequency range	...	...	433.92 MHz
Operating range in open area	...	...	≤ 150 m
LAN ports	...	1 pcs RJ45 100 Mbps	...
Keyfob features	...	...	<ul style="list-style-type: none"> <li>• 4 independent channels</li> <li>• KEELOQ® dynamic code-hopping technology ideal for security demanding applications and high immunity to interference signals</li> </ul>
Inner conductor	4.0 mm <sup>2</sup> - Stranded wire Cu - Tin-plated	...	...
Color	...	...	Black
Rated voltage	600 V / 1000 V AC 1800 V DC	...	...
Outer coating	Ø 5.0 mm - Non-halogen plastic	...	...
Coating color	Black	...	...
LAN+PoE port configuration description	...	<ul style="list-style-type: none"> <li>• xCOAX4-SW : PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+"-": 1, 2 pins; "+/-": 3, 6 pins) or ("+"-": 4, 5 pins; "+/-": 7, 8 pins)</li> <li>• xCOAX4-CAM : Port LAN 10/100Mb or LAN + PoE OUT - PoE (802.3bt) ≤ 60 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W</li> </ul>	...

Transmission range	...	< 1000 m @ Coaxial cable < 100 m @ xCOAX4-SW - Switch PoE < 100 m @ xCOAX4-CAM - IP Camera	...
LED indicators	...	<ul style="list-style-type: none"> <li>• PoE</li> <li>• LAN</li> <li>• Link</li> <li>• 10Mb</li> </ul>	...
Protections	...	<ul style="list-style-type: none"> <li>• Overvoltage - LAN, BNC</li> <li>• Short-circuit - xCOAX4-SW</li> </ul>	...
Main features	<ul style="list-style-type: none"> <li>• UV radiation resistance</li> <li>• Ozone resistance</li> <li>• Hydrolysis resistance</li> <li>• Resistant to oils and aggressive chemicals</li> <li>• Flame resistance (according to VDE 0482-332-2, DIN EN 60332-1)</li> <li>• The insulating layer is made of halogen-free material, which does not produce aggressive fumes during combustion</li> <li>• Increased mechanical strength of the outer coating</li> <li>• Expected lifetime : 25 years</li> </ul>	<ul style="list-style-type: none"> <li>• Plug &amp; Play</li> <li>• Support for IP cameras and network devices</li> <li>• Full transparency for networks</li> <li>• Watchdog function - Coaxial cable</li> </ul>	...
Power supply	...	xCOAX4-SW : <ul style="list-style-type: none"> <li>• 10 ... 58 V DC - cable terminal</li> <li>• PoE 802.3af/at / PASSIVE</li> <li>• The output PoE voltage is equal to the input voltage</li> </ul>	Battery type CR2032 - 3 V (included)
Power consumption	...	1.35 W (total)	...
Housing	...	Plastic (PC)	...
"Index of Protection"	...	IP20	...
Operation temp	...	-25 °C ... 65 °C	...
Weight	...	0.033 kg (single element)	0.03 kg
Dimensions	...	<ul style="list-style-type: none"> <li>• 73 x 52 x 20 mm - xCOAX4-SW</li> <li>• 73 x 52 x 20 mm - xCOAX4-CAM</li> </ul>	64 x 39 x 10 mm
Manufacturer / Brand	...	ATTE	VIDOS
Guarantee	2 years	3 years	3 years