




	IP CAMERA IPC2124LB-SF28KM-G - 3.7 Mpx 2.8 mm UNIVIEW	WIRELESS VIDEO DOORPHONE ATLO-DBC52-TUYA Wi-Fi, Tuya Smart	TERMINAL COVER TBC-09
			
	112.22 USD 112.22 USD	103.32 USD 103.32 USD	0.61 USD 0.61 USD
Application	Power supply adapters of the RSP-200/320 and LRS-200/350 series
Standard	TCP/IP
Sensor	1/3 " Progressive Scan CMOS	SmartSens CMOS - 2 Mpx	...
Material	Plastic, (transparent)
Matrix size	4 Mpx
IR illuminator	...	5 ... 10 m	...
LED illuminator	...	—	...
proximity reader built-in	...	Unique EM 125kHz	...
Wireless transmission range	...	The range limited only by the availability of the Wi-Fi network	...
Resolution	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	1920 x 1080 px - 1080p	...
Wi-Fi standard	...	2.4 GHz IEEE 802.11 b/g/n	...
Lens	2.8 mm	2.0 mm F1.2	...
View angle	• 97 ° (manufacturer data) • 90 ° (our tests result)	140 °	...
Range of IR illumination	30 m
S/N ratio	> 56 dB
RS-485 interface	—
Memory card slot	Micro SD memory cards up to 128GB support (possible local recording)
Supported audio formats	...	G.711	...
Image compression method	Ultra 265 / H.265 / H.264 / MJPEG	H.265 / H.264	...
Alarm inputs / outputs	—
Audio	—
Main stream frame rate	25 fps @ 3.7 Mpx
Network interface	10/100 Base-T (RJ-45)	• 10/100 Mbps Fast Ethernet, RJ-45 socket • 2.4 GHz Wi-Fi	...
Network protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, QoS, SSL / TLS, SNMP

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

WEB Server	Built-in
Max. number of on-line users	32
ONVIF	✓
Mount	...	Surface-mounted	...
Mobile phones support	Access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView	The Tuya Smart free application on Android The Tuya Smart free application on iOS	...
Default IP address	DHCP or 192.168.1.13
Default admin user / password	admin / 123456
Web browser access ports	80, 554
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	80
Port ONVIF	80
Operation temp	...	-20 °C ... 55 °C	...
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream



Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Mirror - Mirror image • Privacy zones - max. 4 • Motion Detection - max. 4 zones • Sharpness - sharper image outlines • Intelligent image analysis : crossing the line (tripwire), intrusion 	<ul style="list-style-type: none"> • ATLO-DBC5/CHIME wireless support • Possibility of expansion with an additional ATLO-DBC5/RELAY wireless relay • Micro SD memory cards up to 256GB support (possible local recording) • Various record modes - users can choose time range for recording during day and set the specific recording mode: recording from motion detection, manual recording, schedule recording, • Motion Detection, • PIR detector, • Indoor proximity cards and key-fobs reader, • ICR - Movable InfraRed filter • Day/night mode, • Microphone built-in, • Speaker built-in, • Bidirectional communication, • Noise and echo reduction • Full support via network • 5 on-line users, • Possibility to work in cloud - you don't need to redirect the ports, • Video PUSH personal messaging - Motion Detection, • Video recording - Motion Detection, Doorbell button, • Automatic events notification via Email messages • Lock control - Relay output • Tamper protections • Google Home, Amazon Echo compliance 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 460 mA 	<ul style="list-style-type: none"> • 12 V DC / 1 A (power adapter included) • 48 V PoE (802.3af) 	...
Power consumption	≤ 5.5 W
Housing	Compact, Metal + Plastic	Aluminum + Plastic (ABS)	...
Color	White	Silver	...
"Index of Protection"	IP67	IP44	...
Vandal-proof	—

Operation temp	-30 °C ... 60 °C
Weight	0.55 kg	<ul style="list-style-type: none"> • 0.22 kg - Wireless Video Doorbell • 0.046 kg - rain cover 	...
Dimensions	165 x 63 x 63 mm	<ul style="list-style-type: none"> • 141 x 87 x 25 mm - Wireless Video Doorbell • 147 x 94 x 40 mm - rain cover 	89 x 10 x 4 mm
Supported languages	Polish, English, Czech, Spanish, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	UNIVIEW
Guarantee	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00