




	WHOLE HOME WI-FI SYSTEM DECO-M4(2-PACK) 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps TP-LINK	SWITCH POE GTX-CLM1-10-8G2G 8-PORT
		
	132.18 CAD 132.18 CAD	213.33 CAD 213.33 CAD
Number of devices included	2 pcs	...
Frequency range	2.4 GHz, 5 GHz	...
Antenna type	2 x Omnidirectional antenna - embedded	...
Standards	IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11 a/n/ac @ 5 GHz	...
Management	...	✓
Baud rates	300 Mbps + 867 Mbps	...
Transmission speed	...	10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink + 8 x Port LAN & PoE
LED indicators	✓	...
DDNS	✓	...
DHCP server	✓	...
Firmware update	Automatic	...
Operation modes	...	<ul style="list-style-type: none"> • N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • S - Extend - Range : 250 m @ 10 Mbps
Default IP address	...	192.168.2.1
LAN ports	2 x 10/100/1000 Mbps 2 x 10/100/1000 Mbps (RJ-45. UTP/STP)	<ul style="list-style-type: none"> • 8 x RJ45 (2 x Hi-PoE + 6 x PoE (802.3af/at)), • 2 x RJ45 - Uplink
Default admin user / password	...	admin / admin
Management interface	Web browser ,	...
Maximal output power	...	<ul style="list-style-type: none"> • 90 W / port Hi-PoE - 1, 2 ports • 30 W / port PoE - 3 ... 8 ports

Transmitter power	max. 20 dBm @ 2.4 GHz max. 23 dBm @ 5 GHz	...
Maximal total power	...	120 W
LED diodes	...	PWR, PoE, Link/Act
Certificates	...	CE, FCC, RoHS
Protections	WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding	Overvoltage \pm 4 kV
Power supply	12 V DC / 1.2 A (power adapter included)	48 ... 57 V DC, Power adapter included
Housing	...	Metal
Main features	<ul style="list-style-type: none"> • The DECO-M4(2-PACK) offers a stable connection with speeds up to 1.167 Gb/s and is compatible with all cable modems, and the entire system can support up to 100 wireless devices in the network • TP-Link Mesh technology: MU-MIMO, Automatic route selection, AP control, Bandwidth control, Beamforming • Port forwarding • Router mode / Access Point mode • Compatible with Amazon Alexa, IFTTT • IPv4/IPv6 • Guest Network - a separate and secure network for guests • Black list • Firewall • WMM (Wi-Fi Multimedia) • Internet access filtering • Access control, parental control • Remote management • Static / dynamic routing • Wireless transmission statistics • Compatible with all Deco models 	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Auto-learning and Auto-aging functions support for MAC addresses • QoS - mechanisms, which provide the high quality of transmission • MTBF (Mean Time Between Faults) : 50000 h
System requirements	<ul style="list-style-type: none"> • Android 4.3 or newer • iOS 9.0 or newer 	...
Operation temp	0 °C ... 40 °C	-10 °C ... 55 °C

Permissible relative humidity	10 % ... 90 % (non-condensing)	...
Weight	0.36 kg	0.45 kg
Dimensions	Ø 91 x 190 mm	185 x 95 x 27 mm
Manufacturer / Brand	TP-LINK	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00