





	BRACKET BR-QME MIKROTIK	VIDEO SEPARATOR WITH OPTO-ISOLATION SV-1000A STANDARD: AHD, HD-CVI	TV OR MONITOR MOUNT ADUX160 ART	INDUSTRIAL POE SWITCH PFS3010-8GT-96-V2 8-PORT DAHUA
				
	7.96 EUR 7.96 EUR	37.68 EUR 37.68 EUR	32.91 EUR 32.91 EUR	116.59 EUR 116.59 EUR
Material	Plastic - anvilNITE
Length of the mounting element	120 mm
The diameter of the fixing element	Ø 40 mm
Standard	...	<ul style="list-style-type: none"> • AHD - 4 Mpx • HD-CVI - 720p • CVBS - PAL / NTSC
Mounting standard	VESA 200 x 200, 300 x 200, 300 x 300, 400 x 300, 400 x 400, 600 x 400	...
Number of inputs	...	1 pcs BNC
Number of outputs	...	1 pcs BNC
Screen size range	32 " ... 80 "	...
Pole diameters range	Ø 35 ... Ø 70 mm
Input impedance	...	75 Ω
Output impedance	...	75 Ω
Bearing capacity	8 kg	...	45 kg	...
Galvanic (optical) isolation between signal inputs and outputs	...	1000 V peak
Opto-isolation between power and signal inputs / outputs	...	1000 V peak
Distance from mounting surface	100 mm	...	65 ... 350 mm	...
Color	Gray	...	Black	...
Gain adjustment	...	-3 dB ... +3 dB
LAN ports	<ul style="list-style-type: none"> • 1 x RJ45 10/100/1000 Base-TX + Hi-PoE / PoE (802.3bt), • 7 x RJ45 10/100/1000 Base-TX + PoE (802.3af/at), • 2 x RJ45 10/100/1000 Base-TX - Uplink ports
Tilt adjustment	0 ° ... 15 °	...
Bandwidth	...	33 MHz / 1 Vpp
Management	—
Horizontal rotation	-40 ° ... 40 °	...
Rotation in the plane of the screen	—	...

Operation modes	<ul style="list-style-type: none"> • Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6 • Extend Off : 100 m, 1000 Mbps @ UTP cat. 5e, 6
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps - 8 LAN & PoE ports, • 10 / 100 / 1000 Mbps - 2 Uplink ports
Maximal output power	<ul style="list-style-type: none"> 30 W / port PoE 60 W / port Hi-PoE 90 W / port PoE 802.3bt
Maximal total power	96 W
MAC addresses table	4k
Main features	High resistance to wind and weather	...	<ul style="list-style-type: none"> • A blockade to prevent the TV/monitor from slipping • Double arm guaranteeing stability and safety • Built-in bubble level for easy installation • In the kit : Expansion plugs, Screws 	<ul style="list-style-type: none"> • PoE power mode : The device supports 8-pin power supply • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • PoE Watchdog / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • Kensington Lock
LED diodes	Power, Link/Act, PoE
Certificates	CE
Power supply	...	12 V DC / 90 mA	...	48 ... 57 V DC / 1.81 A (power adapter included)
Operation temp	-10 °C ... 55 °C
Weight	0.316 kg	0.088 kg	4.25 kg	0.52 kg
Dimensions	102 x 135 x 150 mm	120 x 62 x 30 mm	635 x 420 x (65 ... 350) mm	190 x 100 x 30 mm
Manufacturer / Brand	...	DELTA	ART	DAHUA
Guarantee	2 years	3 years	2 years	5 years