




| | ACCESS CONTROLLER PR622-G ROGER | UNIVERSAL MIDDLE CLAMP PV-KSU/50/B FOR SOLAR PANELS |
|-------------------------------|---|--|
| |  |  |
| | 127.27 EUR 127.27 EUR | 0.92 EUR 0.92 EUR |
| Material | ... | Aluminum |
| Cards support | Unique EM 125kHz | ... |
| Height | ... | 21.5 mm |
| Reading distance of prox-keys | max. 15 cm | ... |
| Hole diameter | ... | 9 mm |
| Autonomous operation | ✓ | ... |
| mounting screw | ... | — |
| Doorbell button | — | ... |
| Relay contacts load | 1.5 A / 30 V | ... |
| Battery backup support | — | ... |
| Keyboard built-in | — | ... |
| Input lines | 3 | ... |
| Color | ... | Black |
| Output lines | 3 | ... |
| Tamper output | ✓ | ... |
| Communication | <ul style="list-style-type: none"> • RS-485 • RACS (Roger) | ... |
| Power supply | 10 ... 15 V DC | ... |
| Average current consumption | 50 mA | ... |
| Main features | <ul style="list-style-type: none"> • Unique EM 125kHz proximity reader built-in • PRT series readers support • 4000 indexed users • History of 32000 events • 99 General Purpose Schedules • 250 access groups • Tamper detection - removing from mounting surface | Ground pins |
| Environment class | IV | ... |
| "Index of Protection" | IP67 | ... |
| Operation temp | -25 °C ... 60 °C | ... |
| Permissible relative humidity | 10 ... 95 % (non-condensing) | ... |
| Weight | 0.15 kg | 0.026 kg |

| | | |
|----------------------|-----------------|-------------------|
| Dimensions | 85 x 85 x 27 mm | 50 x 36 x 24.5 mm |
| Manufacturer / Brand | ROGER | ... |
| Guarantee | 3 years | 2 years |



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00