



	MODULAR PLUG RJ45/6-HAND	POWER DISTRIBUTION UNIT ACAR-XPROTECTOR
		
	634.62 HUF 634.62 HUF	8079.81 HUF 8079.81 HUF
Rated voltage	...	230 V AC / 50 Hz
Connector type	RJ45 (8P8C) Plug	...
Total maximal current	...	10 A
Attachment of connector elements	Pressing	...
Maximal total load	...	2300 W
Wire mounting	Pressing	...
Response time	...	< 25 ns
Number of outlets	...	5 grounded outlets 10A/250V
Application	Twisted-pair cable UTP cat. 6	...
Material	PVC	...
Main features	Very easy and quick installation without any tools	...
Automatic delayed fuse	...	10 A / 250 V
Leak current	...	< 0.5 mA
Nominal voltage of surge suppressor	...	250 V / 50 Hz
Protection level of surge suppressor	...	≤ 1.3 kV (L/N)
Nominal stroke current	...	1 kA (L/N) - (8/20 μ s)
Switch	...	two-way, with light indication
Maximum stroke current	...	4.5 kA (L/N) - (8/20 μ s)
Length of the cable	...	1.45 m
Housing	...	Plastic - non-flammable
Dimensions	53 x 15 x 15 mm	365 x 65 x 52 mm
Weight	0.004 kg	0.51 kg
Guarantee	2 years	2 years