

	EXTENSION CORD WITH GROUNDING PS-3X1.5-20M/ORANGE 20 m	FURNITURE POWER DISTRIBUTION UNIT FPS-3S/CABLE (3 OUTLETS)	ACCESS CONTROLLER MODULE MC16-PAC-EX-1 ROGER
			
	15.96 USD 15.96 USD	28.00 USD 28.00 USD	355.03 USD 355.03 USD
Number of served transitions	1
Inputs	8
Wire gauge	3 x 1.5 mm ²
Outputs	8
Rated voltage	230 V AC / 50 Hz	230 V AC / 50 Hz	...
Total maximal current	16 A	16 A	...
Number of users	max. 12000 - Number of identifiers
Maximal total load	3680 W	3680 W	...
Number of outlets	1 x CEE 7/5	3 grounded outlets 16A/250V CEE 7/5 (Schuko)	...
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.
Fuse	—	—	...
Number of permissions per ID	100
Switch	—	—	...
Length of the cable	20 m	1.8 m	...
Buffer memory	8 000 000 events buffer
MCT readers support	16 pcs
Readers connections	4 pcs - Wiegand / PRT
Housing	...	Plastic + Aluminum, Steel - powder painted	...
Number of login points	2
"Index of Protection"	...	IP20	...
Number of access terminals	4
Number of access zones	2
Color	Orange	Silver + Black	...
Number of alarm zones	2
Number of automation nodes	2
Battery backup support	12 V / 7 Ah

Communication	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RS-485 interface • RACS 5 v2 (Roger)
Main features	...	<ul style="list-style-type: none"> • Fixing in the opening of the table top • Pull-out panel with sockets at the push of a button 	<ul style="list-style-type: none"> • Integrated support in VISO EX software • Functions in the VISO EX system: - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system - unlimited - division of the system into partitions operated by independent operators - tool for integration with RACS5 (API) systems - integration with many systems (elevator systems, building applications, SMS, BMS, PSIM, VMS, Active Directory systems)
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC
Operation temp	5 °C ... 40 °C
Permissible relative humidity	10 % ... 95 % (non-condensing)
Weight	1.57 kg	1.47 kg	0.14 kg
Dimensions	...	<ul style="list-style-type: none"> • 265 x 120 x 77 mm • 250 x 110 x 66 mm - Mounting dimensions (box) 	175 x 72 x 30 mm
Manufacturer / Brand	ROGER
Guarantee	2 years	2 years	3 years