





| | RFID PROXIMITY CARD ATLO-104N | MOUNTING PLATE A19-TS-35/BL-4U | LIGHTING PANEL B-RLF19-1U-B | AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE76H0T-ITMFS(2.8MM) - 5 Mpx Hikvision |
|---|--|---|---|---|
| |  |  |  |  |
| | 4.19 NOK 4.19 NOK | 214.71 NOK 214.71 NOK | 179.74 NOK 179.74 NOK | 794.42 NOK 794.42 NOK |
| Width | ... | 19 " | ... | ... |
| Standard | Unique EM 125kHz | ... | ... | ... |
| Height | ... | 4 U | ... | ... |
| Power | ... | ... | 5 W - LED | ... |
| Compatibility | EM4100/4102 | ... | ... | ... |
| Material | ... | Steel - powder painted | ... | ... |
| Possibility of programming the serial number (ID) | — | ... | ... | ... |
| Ability to write to internal memory | — | ... | ... | ... |
| Standard | ... | ... | ... | AHD / HD-CVI / HD-TVI / CVBS |
| Serial Number overprint | ✓ | ... | ... | ... |
| Sensor | ... | ... | ... | Progressive Scan CMOS |
| Material | ... | ... | Steel, powder painting | ... |
| Matrix size | ... | ... | ... | 5 Mpx |
| Application | ... | ... | Rack 19" | ... |
| Resolution | ... | ... | ... | <ul style="list-style-type: none"> • 2560 x 1944 - 5 Mpx @ AHD / HD-TVI • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI • 1920 x 1080 - 1080p @ HD-TVI • 960 x 576 - 960H @ PAL |
| Range of IR illumination | ... | ... | ... | 30 m |
| IR illuminator power adjustment | ... | ... | ... | Automatic |
| Lens | ... | ... | ... | 2.8 mm |
| Main features | <ul style="list-style-type: none"> • Serial Number Format : 8H10D + WEG24A • Range : ~ 11 cm • The TK-4100 chip | ... | <ul style="list-style-type: none"> • Luminous flux : 405 lm • Light color : Cool, 6500 K • CRI > 80 • "Index of Protection" : IP20 • Length of the cables : - 1.40 m - IEC-320 C7 / CEE 7/16 - 0.25 m - IEC-320 C7 / IEC-320 C7 • Simple and quick device installation | ... |
| View angle | ... | ... | ... | <ul style="list-style-type: none"> • 86 ° (manufacturer data) • 90 ° (our tests result) |
| Video output | ... | ... | ... | AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω |

| | | | | |
|-----------------------|----------------|---------|------------------|---|
| Audio | ... | ... | ... | <ul style="list-style-type: none"> • Microphone built-in • Audio support via coaxial cable - HD-TVI only |
| Main features | ... | ... | ... | <ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • AGC - Automatic Gain Control • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines |
| OSD menu | ... | ... | ... | OSD menu available via recorder |
| Power supply | ... | ... | 220 ... 240 V AC | 12 V DC / 310 mA |
| Power consumption | ... | ... | ... | ≤ 3.7 W |
| Housing | ... | ... | ... | Dome, Metal |
| Color | ... | Black | Black (RAL 9005) | White |
| "Index of Protection" | ... | ... | ... | IP67 |
| Vandal-proof | ... | ... | ... | — |
| Operation temp | ... | ... | ... | -40 °C ... 60 °C |
| Weight | 0.006 kg | 1.03 kg | 0.38 kg | 0.29 kg |
| Dimensions | 86 x 54 x 1 mm | ... | 484 x 45 x 32 mm | 90 x 83 x 79 mm |
| Manufacturer / Brand | ATLO | PULSAR | ... | Hikvision |
| SAP Code | ... | ... | ... | 300613330 |
| Guarantee | 2 years | 2 years | 3 years | 3 years |