






	<a href="#">LED FLOODLIGHT WITH MOTION SENSOR AD-NL-6254BLR4 ADVITI</a>	<a href="#">PATCHCORD RJ45/6/1.5-G-THIN 1.5 m</a>	<a href="#">INSULATION STRIPPER STRF/KLUCZ</a>	<a href="#">IP CAMERA TC-C34UV SPEC:W/E/Y/M/S/4MM Color Maker - 4 Mpx 4 mm TIANDY</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW2501T-Z-A-27135-S2 - 5 Mpx 2.7 ... 13.5 mm - MOTOZOOM DAHUA</a>
					
	67.42 PLN 67.42 PLN	7.12 PLN 7.12 PLN	39.78 PLN 39.78 PLN	1326.00 PLN 1326.00 PLN	896.00 PLN 896.00 PLN
Luminous flux	2400 lm	...	...	...	...
Material	...	...	PET	...	...
Standard	...	...	...	IP	AHD, HD-CVI, HD-TVI, PAL
Light color	Neutral, 4000 K	...	...	...	...
Application	...	...	Coaxial cable RG6 Coaxial cable RG59	...	...
Cable	...	UTP cat. 6 : RJ-45 Plug / RJ-45 Plug	...	...	...
Twilight switch	✓	...	...	...	...
Matrix size	...	...	...	...	5 Mpx
Nominal power	30 W	...	...	...	...
Length of the cable	...	1.5 m	...	...	...
Cable diameter	...	3.8 mm	...	...	...
Power factor	0.8	...	...	...	...
CRI	> 80	...	...	...	...
Sensor	...	...	...	1/1.8 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS
Resolution	...	...	...	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	2880 x 1620 - 5 Mpx - HD-CVI only : Aspect Ratio 16 : 9 , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p - HD-CVI only , 960 x 576 - 960H, PAL
White light LED illuminator range	...	...	...	15 m	...
Memory card slot	...	...	...	Micro SD card support up to 512GB	...
Lens	...	...	...	4 mm	2.7 ... 13.5 mm - Motozoom
Image compression method	...	...	...	S+265 / H.265 / H.264	...
Alarm inputs / outputs	...	...	...	—	...
Main stream frame rate	...	...	...	25 fps @ 4 Mpx 50 fps @ 1080p	...
Main features	<ul style="list-style-type: none"> <li>• LED SMD diodes</li> <li>• LED lifetime 30 000 h</li> <li>• Solid workmanship</li> <li>• PIR detector - Built-in, Range : 4 ... 8 m, Detection angle : 120 °</li> <li>• PIR detection sensitivity adjustment,</li> <li>• Sensitivity adjustment of the twilight sensor : 10 ... 2000 lx,</li> <li>• Lighting time adjustment : 10 ... 600 s,</li> <li>• IK rating : IK04</li> </ul>	<ul style="list-style-type: none"> <li>• A super thin patchcord with an innovative and very convenient clip release</li> <li>• Very easy and quick assembly</li> </ul>	...	...	...
View angle	...	...	...	<ul style="list-style-type: none"> <li>• 94 ° (manufacturer data)</li> <li>• 90 ° (our tests result)</li> </ul>	<ul style="list-style-type: none"> <li>• 113 ° ... 31 ° (manufacturer data)</li> <li>• 110 ° ... 32 ° @ HD-CVI, 94 ° ... 29 ° @ AHD, HD-TVI (our tests result)</li> </ul>
Interface	...	...	...	10/100 Base-TX (RJ-45)	...
Range of IR illumination	...	...	...	...	60 m
WEB Server	...	...	...	Built-in	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

IR illuminator power adjustment	...	...	...	...	Automatic
Max. number of on-line users	...	...	...	2	...
Operation temp	-20 °C ... 50 °C	...	...	...	...
ONVIF	...	...	...	✓	...
Mobile phones support	...	...	...	Port no.: 3000 or access by a cloud (P2P) • Android: Free application <a href="#">EasyLive Plus</a> • iOS (iPhone): Free application <a href="#">EasyLive Plus</a>	...
Access from PC	...	...	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>	...
Video output	...	...	...	...	AHD / HD-CVI / HD-TVI / CVBS - 1 Vpp / 75 Ω
Default IP address	...	...	...	DHCP or 192.168.1.2	...
Audio	...	...	...	• Microphone built-in • Audio transmission via network	• Microphone built-in, • Audio support via coaxial cable - HD-CVI only
Default admin user / password	...	...	...	admin / - The administrator password should be set at the first start	...
S/N ratio	...	...	...	...	> 65 dB
Web browser access ports	...	...	...	80, 433, 3000, 3001, 3002, 23002	...
Mobile client access ports	...	...	...	3000, 3001	...
PC client access ports	...	...	...	3000, 3001	...
Port ONVIF	...	...	...	80	...
Intelligent image analysis	...	...	...	• classification of people and vehicles • crossing the line (tripwire) • video tampering	...
OSD menu	...	...	...	...	OSD menu available via DAHUA recorder



Main features	...	...	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• AGC - Automatic Gain Control</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Color maker - colorful night mode</li> <li>• Corridor mode</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• NAS - Network Attached Storage support</li> <li>• Motion Detection</li> </ul>	<ul style="list-style-type: none"> <li>• Motozoom lens - The control possible only from Dahua recorders in HD-CVI mode</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> <li>• D-ZOOM - Digital Zoom : 4 x</li> <li>• Privacy zones - max. 8</li> </ul>
Power supply	230 V AC	...	...	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 708 mA</li> </ul>	12 V DC / 660 mA
Power consumption	...	...	...	≤ 9.5 W	≤ 7.9 W
Vandal-proof	...	...	...	...	—
Housing	Aluminum	...	...	Compact - Metal	Dome, Aluminum
Color	...	Green	...	White	White
"Index of Protection"	IP44	...	...	IP67	IP67
Mechanical protection class	...	...	...	—	...
Operation temp	...	...	...	-40 °C ... 65 °C	-30 °C ... 60 °C
Weight	0.38 kg	0.032 kg	...	0.91 kg	0.6 kg
Dimensions	155 x 170 x 65 mm	...	...	239 x 90 x 90 mm	Ø 122 x 105 mm
Supported languages	...	...	...	Polish, English, Albanian, Spanish, Korean, Italian, Turkish, Russian, Thai, French, Dutch, Hebrew, Arabic, Vietnamese, German, Ukrainian, Portuguese	...
Manufacturer / Brand	ORNO / ADVITI	...	...	TIANDY	DAHUA
Guarantee	3 years	2 years	2 years	3 years	5 years