




	<a href="#">POE SWITCH / EXTENDER PFT1310 3-PORT</a>	<a href="#">WI-FI SMART PLUG CE1P- EU Wi-Fi, IMOU</a>	<a href="#">POWER CORD CABLE CEE-77/1.5M 1.5 m</a>
			
	7603.81 HUF 7603.81 HUF	3813.33 HUF 3813.33 HUF	1368.57 HUF 1368.57 HUF
Rated voltage	...	220 ... 240 V	...
Maximal total load	...	2500 W	...
Cable	...	...	3 x 0.75 mm <sup>2</sup> / Angular plug (Schuko)
Total maximal current	...	10 A	...
Length of the cable	...	...	1.5 m
Number of outlets	...	1 pcs	...
Voltage	...	...	max. 250 V
Current	...	...	max. 10 A
Socket type	...	CEE 7/3 (Schuko)	...
LAN ports	<ul style="list-style-type: none"> <li>• 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at),</li> <li>• 2 x RJ45 10/100 Base-T + PoE (802.3af)</li> </ul>	...	...
Plug type	...	CEE 7/7	...
Grounding	...	✓	...
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...
Management	—	...	...
LED diodes	LAN, PoE	...	...
Mobile phones support	...	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">IMOU</a></li> <li>• iOS (iPhone): Free application <a href="#">IMOU</a></li> </ul>	...
Transmission speed	10 / 100 Mbps	...	...
Maximal output power	<ul style="list-style-type: none"> <li>• 15.4 W @ port PoE - First device</li> <li>• 3 W @ port PoE - Second device in cascade</li> </ul>	...	...
Power consumption	0.3 W	...	...
Main features	<ul style="list-style-type: none"> <li>• Possibility to connecting in cascade</li> <li>• The device can function as a LAN network and PoE power extender</li> </ul>	<ul style="list-style-type: none"> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control</li> <li>• Energy measurement</li> <li>• ON/OFF button</li> <li>• STATUS indicator</li> </ul>	<ul style="list-style-type: none"> <li>• Very easy and quick assembly</li> <li>• Solid workmanship</li> </ul>
Color	...	White	...

Operation temp	...	-15 °C ... 35 °C	...
Range	100 m - Input 100 m - Output	...	...
Permissible relative humidity	...	≤ 90 %	...
Protections	Overvoltage	...	...
Housing	Plastic, DIN, TS-35 rail mounting	Plastic	...
Power supply	PoE (802.3af/at)	...	...
Operation temp. / Relative humidity	-30 ... 65 °C / 10 ... 90 %	...	...
Manufacturer / Brand	...	DAHUA / IMOU	...
Weight	0.05 kg	0.09 kg	0.15 kg
Dimensions	79 x 52 x 23 mm	Ø 55 x 85 mm	...
Guarantee	2 years	2 years	2 years