




	FLUSH BOX PK-60F/EPN Elektro-Plast	IP SPEED DOME CAMERA OUTDOOR IPC6612SR-X25-VG LightHunter - 1080p 5 ... 125 mm UNIVIEW
		
	19.00 CZK 19.00 CZK	28797.98 CZK 28797.98 CZK
Standard	...	TCP/IP
Number of sections	1	...
Sensor	...	1/2.8 " Progressive Scan CMOS
Matrix size	...	2.1 Mpx
Main features	<ul style="list-style-type: none"> • Flush-mounted, deep, for hollow walls • 2 special screws with holders to fastening to the wall - included 	...
Material	Plastic	...
Resolution	...	1920 x 1080 - 1080p , 1280 x 960 1.3 Mpx , 1280 x 720 720p
Montage hole diameter	Ø 68 mm	...
Lens	...	5 ... 125 mm
View angle	...	54 ° ... 2.6 °
Optical zoom	...	x 25
Digital zoom	...	—
Range of IR illumination	...	150 m
Video output	...	—
Preset rotation speed	...	<ul style="list-style-type: none"> • 180 °/s (horizontal) • 80 °/s (vertical)
Rotation speed (manual control)	...	<ul style="list-style-type: none"> • 2 °/s ... 75 °/s (horizontal) • 2 °/s ... 75 °/s (vertical)
Horizontal rotation range	...	360 ° - continuous
Vertical rotation range	...	-15 ° ... 90 °
RS-485 interface	...	✓
Number of presets	...	1024
Horizontal scan	...	✓
Route settings	...	16
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	2 / 1
Audio	...	<ul style="list-style-type: none"> • External microphone input • Audio output • Bi-directional audio streaming support • Audio detection
Main stream frame rate	...	25 fps @ 1080p

Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	32
ONVIF	...	✓
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support	...	Port 37777 <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	...	DHCP or 192.168.1.13
Default admin user / password	...	admin / 123456
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream

Main features	...	<ul style="list-style-type: none"> • Intelligent Object Tracking • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • Configurable Privacy Zones - 24 • Motion Detection • Tamper signaling • Image rotation and mirror • Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions • Overvoltage protection : 6 kV • Filtering of false alarms based on the recognition of persons and vehicles • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3at), • 12 V DC / 3 A (power adapter included)
Power consumption	...	max. 25 W
Housing	...	Speed Dome, Metal + Plastic
Color	Brick red	White + Black
Operation temp	...	-40 °C ... 65 °C
"Index of Protection"	—	IP66
Vandal-proof	...	—
Weight	0.026 kg	3.5 kg
Dimensions	<p>Ø 60 x 61 mm - Internal dimensions</p> <p>Ø 72 x 62 mm - External dimensions</p>	Ø 220 x 370 mm
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian

Manufacturer / Brand	Elektro-Plast	UNIVIEW
Guarantee	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00