




	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1500R-Z-IRE6-A-2712-S2 - 5 Mpx 2.7 ... 12 mm - MOTOZOOM DAHUA</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1500TLM-IL-A-0280B-S2 - 5 Mpx 2.8 mm DAHUA</a>	<a href="#">DIRECTIONAL ANTENNA CDMA-5/400-470/FME</a>
			
	1640.58 NOK 1640.58 NOK	1046.95 NOK 1046.95 NOK	178.63 NOK 178.63 NOK
Frequency range	...	...	400 ... 470 MHz
Connector	...	...	FME Socket
Standard	AHD / HD-CVI / HD-TVI / PAL	AHD, HD-CVI, HD-TVI, CVBS	...
Gain	...	...	max. 6 dBi
Sensor	1/2.7 " Progressive Scan CMOS	Progressive Scan CMOS	...
Impedance	...	...	50 Ω
Matrix size	5 Mpx	5 Mpx	...
Polarization	...	...	Vertical
Main features	...	...	<ul style="list-style-type: none"> <li>• Length of the cable : 5 m</li> <li>• Number of elements : 5</li> <li>• Very easy and quick assembly</li> <li>• Small dimensions</li> </ul>
Resolution	<ul style="list-style-type: none"> <li>• 2880 x 1620 - 5 Mpx @ HD-CVI - 25 fps : Aspect Ratio 16 : 9,</li> <li>• 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI - 25 fps</li> <li>• 1920 x 1080 - 1080p @ HD-CVI - 25 fps</li> <li>• 960 x 576 - 960H @ PAL</li> </ul>	<ul style="list-style-type: none"> <li>• 2880 x 1620 - 5 Mpx @ HD-CVI @ 25 fps - Aspect Ratio 16 : 9 ,</li> <li>• 2560 x 1440 - 3.7 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps</li> <li>• 1920 x 1080 - 1080p @ HD-CVI @ 25 fps ,</li> <li>• 960 x 576 - 960H @ PAL @ 25 fps</li> </ul>	...
White light LED illuminator range	...	20 m	...
Lens	2.7 ... 12 mm - Motozoom	2.8 mm	...
Video output	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	...
View angle	<ul style="list-style-type: none"> <li>• 107 ° ... 34 ° (manufacturer data)</li> <li>• 102 ° ... 35 ° @ HD-CVI (our tests result)</li> <li>• 90 ° ... 31 ° @ AHD / HD-CVI (our tests result)</li> </ul>	<ul style="list-style-type: none"> <li>• 106 ° (manufacturer data)</li> <li>• 101 ° (our tests result)</li> </ul>	...
S/N ratio	> 65 dB	...	...
Range of IR illumination	60 m	20 m	...
IR illuminator power adjustment	Automatic	Automatic	...
Audio	Microphone built-in - HD-CVI only	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Audio support via coaxial cable - HD-CVI only</li> </ul>	...

Main features	<ul style="list-style-type: none"> <li>• Motozoom lens - The camera does not have auto-focus function</li> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• AGC - Automatic Gain Control</li> <li>• ICR - Movable InfraRed filter</li> <li>• Privacy zones - max. 8</li> <li>• Mirror - Mirror image</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul>	<ul style="list-style-type: none"> <li>• Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Privacy zones - max. 8</li> <li>• Mirror - Mirror image</li> <li>• Auto White Balance</li> <li>• Sharpness - sharper image outlines</li> </ul>	...
Vandal-proof	...	—	...
OSD menu	✓	✓	...
Power supply	12 V DC / 820 mA	12 V DC / 260 mA	...
Power consumption	≤ 9.8 W	≤ 3.1 W	...
Housing	Compact, Metal	Dome - Metal	...
Color	White	White	...
"Index of Protection"	IP67	IP67	...
Operation temp	-30 °C ... 60 °C	-40 °C ... 60 °C	...
Weight	0.55 kg	0.32 kg	0.53 kg
Dimensions	210 x 90 x 90 mm	Ø 94 x 86 mm	570 mm
Manufacturer / Brand	DAHUA	DAHUA	...
Guarantee	3 years	3 years	2 years