

	NVR BCS-NVR0801X5ME-P 8 CHANNELS +8-PORT SWITCH POE	SOLAR PANEL SP-100-MS RIGID IN AN ALUMINIUM FRAME	FLASH DRIVE USB-P629-32-32GB 32 GB USB 3.2 Gen 1 DAHUA	BATTERY 12.8V/25AH/LiFePO4-EP EUROPOWER
				
	136095.24 HUF 136095.24 HUF	25365.71 HUF 25365.71 HUF	2706.67 HUF 2706.67 HUF	92560.00 HUF 92560.00 HUF
Capacity	32 GB	...
Battery capacity	25 Ah
Standard	TCP/IP
Maximum power	...	100 W
Rated voltage	12.8 V
Maximum Power Current (I _{mp})	...	4.46 A
Battery charging current	max. 12 A
Maximum Power Voltage (V _{mp})	...	22.4 V
Connector type	USB 3.2 Gen 1 - USB-C / USB-A	...
Battery type	LiFePO ₄ , lithium-iron-phosphate battery
Short-circuit Current (I _{sc})	...	4.97 A
Open-circuit Voltage (V _{oc})	...	26.4 V
Write transfer rate	6 ... 100 MB/s	...
Battery lifetime	> 2000 cycles @ 80 % DoD
Length of the cables	...	2 x 0.45 m
Connector	M5 screw
Cell Type	...	Monocrystalline
Panel Structure	...	Rigid in an aluminum frame
Read speed	20 ... 150 MB/s	...
Main features	<ul style="list-style-type: none"> • Light and durable construction • Can be rotated to select USB-C / USB-A connector 	...
Supported resolutions	8 @ 2560 x 1920 px, 8 @ 2048 x 1536 px, 8 @ 1920 x 1080 px, 8 @ 1280 x 720 px, 8 @ 704 x 576 px
Video outputs	1 pcs HDMI 1 pcs VGA
Audio support	8 Channels - Audio from cameras, Bi-directional audio streaming support
Audio inputs	1 pcs Microphone - CINCH
Audio outputs	1 pcs - CINCH
Image compression method	H.264 / MJPEG
Maximal total frame rate	200 fps @ 2560 x 1920 px, 200 fps @ 2048 x 1536 px, 200 fps @ 1920 x 1080 px, 200 fps @ 1280 x 720 px, 200 fps @ 704 x 576 px
Supported hard drives	1 x 6 TB SATA
Recording modes	Manual, Motion Detection, Schedule
Network protocols	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, ONVIF
ONVIF	2.4
External storage devices backup	Backup to USB drive (pendrive, external drive)
Searching and playback the records	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function
Network functions	Full support via network, Remote records copying, Web-Server built-in max. 128 on-line users
Bitrate	max. 80 Mbps

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default admin user / password	admin / admin
Default IP address	192.168.1.108
Web browser access ports	80, 37777
PC client access ports	37777
Mobile client access ports	37777
Port ONVIF	80
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Alarm inputs / outputs	—
PTZ control	IP Speed Dome Cameras
Motion Detection	22 x 18 motion zones
Mouse support	✓
IR remote controller in the set	✓
Switch PoE	8-port PoE Switch built-in, 25.5 W / Channel, PoE (802.3af/at)
Power supply	48 V DC / 2 A (power adapter included)
Maximum total switch load	75 W (at full load) NVR=10W + HDD=10W
Weight	1.27 kg	5.96 kg	...	2.9 kg
Dimensions	325 x 250 x 55 mm	1190 x 450 x 30 mm	69 / 73 x 16 x 12 mm	181 x 76 x 166 mm
Supported languages	English, Polish
Country of origin	China
Manufacturer / Brand	BCS	SolarFam	DAHUA	EUROPOWER
Guarantee	2 years	2 years	5 years	5 years