



	SWITCHING ADAPTER SDR-120-24 MEAN WELL	SWITCH POE APTI- POE0802G-120W-ECO 8- PORT
		
	280.35 PLN 280.35 PLN	192.00 PLN 192.00 PLN
Adapter type	Switching	...
Power voltage	<ul style="list-style-type: none"> • 88 ... 264 V AC • 124 ... 370 V DC 	...
Output voltage	24 V DC	...
Output voltage adjustment	24 ... 28 V DC	...
LAN ports	...	<ul style="list-style-type: none"> • 8 x RJ45 10/100 Base-TX (8 x PoE (802.3af/at)), • 2 x RJ45 100/1000 Base-TX - Uplink
Maximal load	5 A	...
Output power	120 W	...
Instantaneous maximum power	180 W - 3 s (max)	...
Number of outputs	1 pcs	...
Transmission speed	...	<ul style="list-style-type: none"> • 10 / 100 Mbps : 8 x Port LAN & PoE, • 100 / 1000 Mbps : 2 x Port RJ45 (Uplink)
Efficiency	88 %	...
Housing type	DIN	...
Maximal output power	...	30 W / port PoE - 1 ... 8 ports
Relay output	1 pcs - DC OK	...
Maximal total power	...	120 W
MAC addresses table	...	2k
Management	...	—
Protections	<ul style="list-style-type: none"> • Short-circuit • Overload • Overvoltage • Overheat 	...
Operation modes	...	E+V - Extend On : 250 m @ 10 Mbps - 1 ... 4 ports
Operation temp. / Relative humidity	-25 °C ... 70 °C / 20 ... 95 %	...
LED diodes	...	Power, Extend, Link/Act, PoE

Main features	...	<ul style="list-style-type: none"> • Power supply PoE, Endspan mode support : 1-2(+), 3-6(-) • EXTEND mode - 1 ... 4 ports • Port PoE Priority • Auto-learning and Auto-aging functions support for MAC addresses • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • Mounts for mounting the device in the RACK 10" system
Certificates	...	CE
Housing	...	Metal
Power supply	...	110 ... 240 V AC, 50 / 60 Hz
Operation temp	...	-10 °C ... 55 °C
Weight	0.62 kg	0.68 kg
Dimensions	125 x 124 x 41 mm	200 x 122 x 45 mm
Manufacturer / Brand	MEAN WELL	APTI
Guarantee	3 years	2 years