



	EXTENDER VGA+AU/UTP	SWITCHING ADAPTER PS65-15-DIN ACO
		
	62.63 EUR 62.63 EUR	58.57 EUR 58.57 EUR
Application	...	ACO Video Doorphones
Adapter type	...	Switching
Power voltage	...	100 ... 240 V AC
Output voltage	...	15 V DC
Output voltage adjustment	...	—
Maximal load	...	4 A
Output power	...	65 W
Number of outputs	...	2 pcs
Efficiency	...	≤ 91 %
Housing type	...	DIN
Protections	...	<ul style="list-style-type: none"> • Short-circuit • Overload • Overheat
Manufacturer / Brand	...	ACO
Device type	Active / Transmitter Active / Receiver	...
Inputs	<ul style="list-style-type: none"> • Video - VGA • Audio - stereo (Jack) UTP	...
Outputs	<ul style="list-style-type: none"> • Monitor - VGA • UTP • Audio - stereo (Jack) • Monitor - VGA • Audio - stereo (Jack) 	...
Power supply	12 V DC / 1000 mA (power adapter included) 12 V DC / 1000 mA (power adapter included)	...
Video transmission range	max. 140 m max. 140 m	...
Symmetrical socket impedence	100 Ω 100 Ω	...
Connectors type	<ul style="list-style-type: none"> • 2 x VGA - Socket • 2 x Jack 3.5 mm socket • 1 x VGA Socket • 1 x Jack 3.5 mm socket 	...

Symmetrical socket type	RJ-45 (8-pin, 4 pairs) Socket RJ-45 (8-pin, 4 pairs) Socket	...
Weight	0.2 kg 0.1 kg	0.22 kg
Dimensions	105 x 95 x 27 mm 72 x 46 x 24 mm	70 x 91 x 59 mm
Main features	<ul style="list-style-type: none"> • UTP cat. 5, 5e, 6 • Signal correction • Metal housing 	...
Resolution	<ul style="list-style-type: none"> • 1280 x 1024 px SXGA @ 60 m (manufacturer data) • 1024 x 768 px XGA @ 76 m (manufacturer data) • 800 x 600 px SVGA @ 106 m (manufacturer data) • 640 x 480 px VGA @ 137 m (manufacturer data) • 1920 x 1080 px Full HD @ 45 m (our tests result) • 1024 x 768 px XGA @ 100 m (our tests result) 	...
Bandwidth	≤ 60 MHz DC	...
Insertion loss	< 3 dB	...
Return loss	max. -15 dB	...
Grounding	via grounding bolt	...
Operation temp	0 °C ... 55 °C	...
Permissible relative humidity	≤ 95 %	...
Guarantee	2 years	3 years

