



	FIBER OPTIC CABLE GYFXTH-4/500M	PATCHCORD RJ45/0.5-GREY 0.5 m
		
	2274.47 NOK 2274.47 NOK	8.45 NOK 8.45 NOK
Fiber type	Single-mode, ITU-T G.652.D, U-DQ(ZN)BH	...
Number of fibers	4 pcs	...
Cable	...	UTP cat. 5e : RJ 45 Plug / RJ 45 Plug
Cable diameter	5.8 mm	...
Color	...	Gray
Length of the cable	...	0.5 m
Length	It is sold in 500 m spools	...
Weight	...	0.020 kg
Buffer diameter	250 µm	...
Maximum pulling force	2000 N (dynamic)	...
Minimal bend radius	116 mm (during installation)	...
Main features	<ul style="list-style-type: none"> • rodent protected • the LSZH (or LSOH) jacket - zero halogen, flame retardant and low smoke • gel-filled central tube • reinforced by aramid yarn • ripcord making it easier to cut the outer sheath of the cable 	<ul style="list-style-type: none"> • Very easy and quick assembly • Corrosion resistance
Application	<ul style="list-style-type: none"> • due to the small size and flexibility, the cables are ideal for installation in cable ducts • it is used in modern FTTH and FTTB systems, in server rooms, between buildings installations • universal fiber optic cables intended for horizontal connections in buildings and outside buildings in secondary sewage system 	...
Operation temp	-40 °C ... 60 °C	...
Installation temperature	-5 °C ... 70 °C	...
Guarantee	2 years	2 years