



	<a href="#">END CLAMP PV-KK/40-50/B FOR SOLAR PANELS 40 mm</a>	<a href="#">IP CAMERA DS-2CD1623G2-LIZU(2.8-12MM) ColorVu - 1080p - MOTOZOOM Hikvision</a>
		
	218.10 HUF 218.10 HUF	108952.38 HUF 108952.38 HUF
Material	Aluminum	...
Standard	...	IP
Height	40 mm	...
Hole diameter	9 mm	...
mounting screw	—	...
Resolution	...	1920 x 1080 - 1080p 1280 x 720 - 720p
Sensor	...	1/2.9 " Progressive Scan CMOS
Lens	...	2.8 ... 12 mm - Motozoom
View angle	...	102 ° ... 31 °
White light LED illuminator range	...	50 m
Range of IR illumination	...	50 m
Memory card slot	...	Micro SD memory cards up to 512GB support (possible local recording)
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Audio transmission via network</li> </ul>
Main stream frame rate	...	25 fps @ 1080p
Interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	6
ONVIF	...	✓
Main features	...	<ul style="list-style-type: none"> <li>• Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Horizontal mirror image</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Configurable Privacy Zones</li> <li>• Sharpness - sharper image outlines</li> <li>• video tampering</li> </ul>

Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <a href="#">Hik-Connect</a> • iOS: Free application <a href="#">Hik-Connect</a>
Default IP address	...	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
Power supply	...	• PoE (802.3af), • 12 V DC / 900 mA
Power consumption	...	• ≤ 12.9 W @ PoE • ≤ 11 W @ 12 V DC
Housing	...	Compact, Metal + Plastic
Color	Black	White
"Index of Protection"	...	IP67
Mechanical protection class	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	0.26 kg	0.7 kg
Dimensions	50 x 43 x 30 mm	Ø 105 x 252 mm
Supported languages	...	English, Ukrainian
Manufacturer / Brand	...	Hikvision
SAP Code	...	311325224
Guarantee	2 years	3 years