




	FLUSH BOX PK-60/60M	ACCESS CONTROLLER WITH FACE RECOGNITION DS-K1T341AM-S - 720p Hikvision	POE SWITCH / EXTENDER PFT1310 3-PORT
			
	0.28 CHF 0.28 CHF	454.49 CHF 454.49 CHF	18.15 CHF 18.15 CHF
Sensor	...	CMOS	...
Matrix size	...	2 Mpx	...
Resolution	...	1280 x 720 - 720p	...
Cards support	...	13.56 MHz S50	...
LAN ports	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at), • 2 x RJ45 10/100 Base-T + PoE (802.3af)
Face recognition distance	...	0.3 m ... 1.5 m	...
Management	—
Memory	...	<ul style="list-style-type: none"> • Memory of 1500 face templates • Memory of 1500 RFID cards • Non-volatile log buffer of the last 150 000 events 	...
LED diodes	LAN, PoE
Standard	...	TCP/IP	...
Transmission speed	10 / 100 Mbps
IR illuminator	...	—	...
LED illuminator	...	—	...
Video output	...	—	...
RS-485 interface	...	✓	...
Memory card slot	...	—	...
Alarm inputs / outputs	...	—	...
Maximal output power	<ul style="list-style-type: none"> • 15.4 W @ port PoE - First device • 3 W @ port PoE - Second device in cascade
Audio	...	Speaker built-in	...
Network interface	...	10/100/1000 Mbps (RJ-45)	...
Main features	Mounting screws - included	...	<ul style="list-style-type: none"> • Possibility to connecting in cascade • The device can function as a LAN network and PoE power extender
Network protocols	...	TCP/IP, ISUP, ISAPI	...

WEB Server	...	Built-in	...
ONVIF	...	—	...
Range	100 m - Input 100 m - Output
Default IP address	...	192.168.1.64	...
Protections	Overvoltage
Default admin user / password	...	admin / - The administrator password should be set at the first start	...
Web browser access ports	...	80	...
PC client access ports	...	port 8000	...
Operation temp. / Relative humidity	-30 ... 65 °C / 10 ... 90 %
Main features	...	<ul style="list-style-type: none"> • 4.3 " capacitive touch screen • Mechanical tamper protection • WDR - Wide Dynamic Range • AI detection : Face recognition • Configuration and management from the iVMS-4200 application • Port USB • Recording of information about Time&Attendance • Possibility to open the gate using a QR code • Door lock control output • Possibility to connect an exit button and a reed switch to control the door status 	...
Power supply	...	12 V DC / 2 A (power adapter included)	PoE (802.3af/at)
Power consumption	...	≤ 24 W	0.3 W
Housing	...	Metal	Plastic, DIN, TS-35 rail mounting
Color	...	Black / Silver	...
"Index of Protection"	IP20	—	...
Operation temp	...	-30 °C ... 60 °C	...
Weight	...	0.31 kg	0.05 kg

Dimensions	Ø 73 x 60 mm	173 x 83 x 23 mm (without bracket)	79 x 52 x 23 mm
Supported languages	...	English, German, French, Polish, Czech, Hungarian, Bulgarian, Serbian, Slovenian, Albanian	...
Manufacturer / Brand	...	Hikvision	...
SAP Code	...	302917454	...
Guarantee	2 years	3 years	2 years