




	DOOR CONTROLLER ACCO-KP2 SATEL	ACCESS CONTROLLER WITH FACE RECOGNITION + READER ATLO-FR-601	ACCESS CONTROLLER PR102DR-BRD ROGER
			
	117.99 USD 117.99 USD	51.83 USD 51.83 USD	89.86 USD 89.86 USD
Environment class	I
Face recognition distance	...	0.5 m ... 1 m (max 1000 faces in the database)	...
Battery backup support	—
Operation modes	<ul style="list-style-type: none"> • Autonomous operation, • Work in the ACCO/ACCO NET system
Input lines	12	...	2
RFID proximity reader built-in	...	Unique EM 125kHz - Number of supported proximity cards : 10 000	...
Output lines	12	...	2
Fingerprint reader built-in	...	Memory of 600 fingerprint patterns	...
Range of IR illumination	...	5 m	...
White light LED illuminator range	...	—	...
Video output	...	—	...
Wiegand interface	...	✓	...
Outputs rating	<ul style="list-style-type: none"> • 50 mA / 12 V DC - (OUT 1-12) • 0.5 A / 12 V DC - (+G 1-4)
RS-485 interface	...	—	...
Relay switching voltage	250 V AC, 30 V DC
Alarm inputs / outputs	...	0 / 1 - Relay output	...
Relay contacts load	8 A	...	1.5 A / 30 V
Communication	RS-485	...	<ul style="list-style-type: none"> • RS-485 • RACS (Roger)
Operation temp	5 °C ... 40 °C

Main features	...	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera • Identification modes : Face recognition, Fingerprint, Proximity identifier Unique EM 125kHz, Any combination of the above • Wiegand 26 • LEDs and buzzer • Buzzer for acoustic signaling of some system events 	...
Power consumption	...	$\leq 3.6 \text{ W}$ (operation) $\leq 2.2 \text{ W}$ (standby)	...
Housing	...	Aluminum + Tempered glass, Vandal-proof	...
Color	...	Silver + Black	...
"Index of Protection"	...	IP65	...
Operation temp	...	-40 °C ... 60 °C	...



Main features	<ul style="list-style-type: none"> • 5 programmable input lines NO/NC • Additional dedicated inputs for connecting readers, monitoring the presence of readers, and connecting the tamper circuit • power input • 2 programmable low-current output lines OC • Additional outputs dedicated to connecting readers • Relay output to control the electromagnetic lock, gate controllers or other devices that activate the door • 4 power outputs 12 V/0.5 A • Support for single door with entry and exit authorization, <ul style="list-style-type: none"> • 1024 users • Possibility to add different privileges to the users • Identification: Card and/or PIN, Dallas iButton • History of 24 576 events • Recording of information about Time&Attendance • Up to 256 access calendars, weekly schedules, daily schedules, time frames • Holiday access schedules • Function to prevent of multiple use of the same code/card to gain access (anti-passback) • Scheduled door locking and unlocking • Limiting of accesses • Compliance with the EM-MARIN, Wiegand 26-56bit, DALLAS protocol • micro USB socket - The ability to firmware upgrade • Its own clock with battery backup • LED indicators displaying the device's operating status • APS power socket - SATEL power adapter (not included) 	...	<ul style="list-style-type: none"> • PRT series readers support • 4000 indexed users • History of 32000 events • Real-time clock and calendar • Remote programming from PC
Power supply	12 V DC	12 V DC	10 ... 15 V DC



Current consumption	• 110 mA (Standby mode) • 480 mA (operation)
Permissible relative humidity	93 % ± 3 %	...	10 ... 95 % (non-condensing)
Weight	0.11 kg	0.38 kg	0.04 kg
Dimensions	142 x 71 x 17 mm	170 x 70 x 24 mm	80 x 54 x 18 mm
Manufacturer / Brand	SATEL	ATLO	ROGER
Guarantee	2 years	2 years	3 years