



	SET OF CABLE QUICK-CONNECTORS OR-SZ-8007 123 PCS ORNO	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW1800TH-I8-0360B - 8.3 Mpx 3.6 mm DAHUA
		
	25.94 EUR 25.94 EUR	109.50 EUR 109.50 EUR
Application	Connecting cables	...
Connector type	Push-in splicing	...
Contact material	100 % Cu + Sn	...
Standard	...	AHD, HD-CVI, HD-TVI, CVBS
Sensor	...	1/2.7 " Progressive Scan CMOS
Material	PC + Nylon 66	...
Matrix size	...	8.3 Mpx
Resolution	...	3840 x 2160 - 8.3 Mpx @ HD-CVI @ 25 fps , 3840 x 2160 - 8.3 Mpx @ HD-CVI / HD-TVI / AHD @ 15 fps , 2592 x 1944 - 5 Mpx @ HD-CVI @ 20 fps , 2560 x 1440 - 3.7 Mpx @ HD-CVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps
Lens	...	3.6 mm
Number of pcs. in package	123 pcs (total) • Push-in splicing - 30 pcs - 2 x 0.75 - 2.5 mm ² - 30 pcs - 3 x 0.75 - 2.5 mm ² - 25 pcs - 4 x 0.75 - 2.5 mm ² - 20 pcs - 5 x 0.75 - 2.5 mm ² - 10 pcs - 6 x 0.75 - 2.5 mm ² - 8 pcs - 8 x 0.75 - 2.5 mm ²	...
Main features	• high quality • quick connection of cables	...
View angle	...	• 87 ° (manufacturer data) • 83 ° (our tests result)
Range of IR illumination	...	80 m
IR illuminator power adjustment	...	Automatic
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio	...	—

OSD menu	...	OSD menu available via DAHUA recorder
Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance
Power supply	...	12 V DC / 500 mA
Power consumption	...	≤ 6 W
Housing	...	Compact, Plastic + Metal
Color	...	White + Black
"Index of Protection"	...	IP67
Operation temp	...	-40 °C ... 60 °C
Weight	...	0.41 kg
Dimensions	...	241 x 91 x 90 mm
Manufacturer / Brand	ORNO	DAHUA
Guarantee	...	3 years