



	IP SPEED DOME CAMERA OUTDOOR OMEGA-50P36-24 - 5 Mpx 4.6 ... 165 mm	WORK GLOVES WG-422/M Bee-Smart WONDER GRIP
		
	645.09 EUR 645.09 EUR	5.63 EUR 5.63 EUR
Standard	TCP/IP	...
Sensor	1/2.8 " Sony CMOS IMX335	...
Matrix size	5 Mpx	...
Application	...	<ul style="list-style-type: none"> • Construction and public works, • Warehousing - packing and logistics, • DIY, • Assembly
Material	...	Polyester + latex coating (palm coated)
Resolution	2592 x 1944 - 5 Mpx , 2560 x 1440 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	...
Lens	4.6 ... 165 mm	...
Main features	...	<ul style="list-style-type: none"> • Thermal protection : 100 °C (X1XXXX), • Ergonomics and comfort • High grip • Soft coating
View angle	<ul style="list-style-type: none"> • 61 ° ... 1.9 ° (manufacturer data) • 52 ° ... 3.1 ° (our tests result) 	...
Optical zoom	x 36	...
Auto IR illuminator	Adaptive adjusting of the IR illuminator power to the lens zoom and outdoor light conditions	...
Range of IR illumination	240 m - Laser IR + LED IR	...
Video output	—	...
Supported norms	...	<ul style="list-style-type: none"> • EN 388:2016 - Mechanical protection 3131X • EN 407:2004 - Thermal protection X1XXXX
Size	...	8 / M
Rotation speed (manual control)	<ul style="list-style-type: none"> • 1 °/s ... 200 °/s (horizontal) • 1 °/s ... 100 °/s (vertical) 	...
Horizontal rotation range	360 ° continuous	...

Vertical rotation range	0 ° ... 93 °	...
Audio	<ul style="list-style-type: none"> • Microphone built-in • Audio transmission via network 	...
RS-485 interface	—	...
Number of presets	255	...
Horizontal scan	✓	...
Image compression method	H.265+ / H.265 / H.264+ / H.264	...
Protections	Overvoltage	...
Alarm inputs / outputs	—	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP	...
Main stream frame rate	<ul style="list-style-type: none"> • 20 fps @ 5 Mpx • 25 fps @ 4 Mpx 	...
WEB Server	Built-in	...
ONVIF	✓	...
Mobile phones support	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision • iOS (iPhone): Free application BitVision 	...
Default IP address	192.168.1.168	...
Default admin user / password	admin / admin The administrator password should be set at the first start	...
Web browser access ports	80	...
Port ONVIF	8999	...
RTSP URL	rtsp://ip_address/1/h264major - Main stream rtsp://ip_address/1/h264minor - Sub stream	...
Route settings	8	...
OSD menu	preset 95	...

Main features	<ul style="list-style-type: none"> • Intelligent image analysis, intrusion, motion detection based on human detection, video tampering • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • Parking action - this function enables to locate the camera to specific position automatically if operator doesn't operate the controller for some time • ICR - Movable InfraRed filter • BLC - configurable Back Light Compensation • Auto White Balance • IR illuminator optimization • Mirror - Mirror image • Privacy zones - max. 4 	...
Power supply	12 V DC / 5 A (power adapter included)	...
Power consumption	≤ 29 W	...
Housing	Speed Dome, Metal	...
Color	White + Black	Black + Blue
"Index of Protection"	IP66	...
Operation temp	-40 °C ... 60 °C	...
Weight	4.43 kg (with bracket)	...
Dimensions	265 x 357 x 405 mm (with bracket)	...
Supported languages	Polish, English, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian	...
Manufacturer / Brand	OMEGA	WONDER GRIP
Guarantee	2 years	...