











	TRIPE SMART LIGHT TOUCH SWITCH AT10-TB3-TUYA Wi-Fi_Tuya Smart	INSULATION STRIPPER HT-332	ACCESS CONTROLLER ASC2204B-S.DAHUA	SIDE MOUNTING PANEL FOR RACK CABINETS ZMP-1-800	GLUE STICKS FOR SOLDERING GUNS MCE434 12 PCS	MULTISOCKET PLUG LE39400 3680 W LEGRAND	PATCHCORD RJ45/7/10-EL 10.0 m UNITEK	RJ45 PLUG INTERNAL SHIELD RJ450VP.NJNF	PATCHCORD IUC PATCH-SM-RJ45-BL 8.0 m UBIQUITI	COUPLER CG-5.5
										
	8.99 GBP 8.99 GBP	2.61 GBP 2.61 GBP	241.20 GBP 241.20 GBP	21.03 GBP 21.03 GBP	3.22 GBP 3.22 GBP	4.90 GBP 4.90 GBP	8.47 GBP 8.47 GBP	0.05 GBP 0.05 GBP	8.89 GBP 8.89 GBP	0.50 GBP 0.50 GBP
Application
Width	548 - 570 mm
Number of served transitions	4 (one-way)
Packaging	12 pcs
Height	200 mm
Support	DAHUA
Dimensions of the sticks	Ø 11 x 150 mm
Maximal total load	3680 W
Material	Aluminum - powder painted
Number of supported readers	4 pcs
Battery backup support	---
Cable	SSTP cat. 7 : RJ-45 - Plug / RJ-45 - Plug	...	UTP cat. 6 : RJ-45 - Plug / RJ-45 - Plug	...
Rated voltage	100 ... 240 V AC, 50 / 60 Hz	230 V / 50 Hz
Total maximal current	16 A (6 A socket)
Output lines	5 pcs - Relay
Number of outlets	4 pcs
Application	Works with lighting - switching on/off	Coaxial cable RG58 RG59 RG6	Coupler Socket 2.1 : 5.5 mm Socket 2.1 : 5.5 mm
Connector type
Length of the cable	10.0 m	...	8.0 m	...
Maximum power	300 W (for each output)
Material	...	PET	Rubber	...	Metal / PET
Rated current	max. 10 A
Socket type	2P (flat)
Number of buttons	3 (touch)
Number of outputs	3
Communication
Plug type	CEE 7/4 (Schuko)
Connector type	screw terminals
Grounding
Power supply	12 V DC / 1.4 A
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Mobile phones support	• The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Default IP address	192.168.0.2
Default admin user / password	admin / The administrator password should be set at the first start
Manufacturer / Brand	DAHUA	LEGRAND	UNITEK	...	UBIQUITI	...
Main features	<ul style="list-style-type: none"> Local control by physical button, schedule, timer, Setting scenarios by different events, remote access, voice control, LED indication Backlit, touch control panel The product does not fit standard mounting boxes with a diameter of 60 mm 	Left shield width adjustment	<ul style="list-style-type: none"> 100000 indexed users History of 150000 events Remote programming from PC Function of protection against multiple use of the same card for access (anti-passback) Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress 	...	<ul style="list-style-type: none"> Universal sticks for glue guns A wide range of applications 	...	<ul style="list-style-type: none"> 10 Gigabit Ethernet Very flexible Ultra-thin 2.3 mm thick patchcord 100% copper conductor Gold-plated connector prevents the oxidation of contacts SSTP - double shielded twisted-pair cable Corrosion resistance Environmental immunity 	<ul style="list-style-type: none"> Very flexible Ultra-thin 3 mm thick patchcord Very easy and quick assembly Corrosion resistance 	<ul style="list-style-type: none"> Very easy and quick assembly Corrosion resistance 	
Housing	Plastic + Acrylic glass (plexiglass)	Plastic
Color	White	Black	Transparent	White / Light gray	Black	Blue	Blue	...
Operation temp	-20 °C ... 50 °C	...	30 °C ... 60 °C
Permissible relative humidity	≤ 90 %	...	max. 95 % (non-condensing)
Weight	0.142 kg	...	0.354 kg	0.59 kg	0.014 kg (single element)	0.104 kg	0.23 kg	0.001 kg	0.082 kg	0.006 kg
Dimensions	86 x 86 x 34 mm	...	207 x 116 x 52 mm	86 x 74 x 72 mm	...	27 x 12 x 15 mm	Ø 10 x 40 mm	...
Guarantee	2 years	2 years	3 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00