






	LASER FIBER TESTER BML-209-20 650 nm > 20 mW > 10 km TriBrer	TWO-COMPONENT GEL- GUM GEL-GUM-500 RayTech	MONITOR DESK MOUNT BRATECK-LDT66-C01	MAIN UNIT MODULE OF THE IP CAMERA IPC-HUM8231-E1 - 1080p DAHUA	SLOTTED SCREWDRIVER 3.5 ST-STHT16152-0 STANLEY
					
	20.31 EUR 20.31 EUR	23.85 EUR 23.85 EUR	8.96 EUR 8.96 EUR	274.52 EUR 274.52 EUR	2.18 EUR 2.18 EUR
Standard	TCP/IP	...
Optical wavelength	650 nm
Tip size	3.5 mm
Sensor	---	...
Optical output power	> 20 mW
Arrowhead length	75 mm
Matrix size	---	...
Operation range	> 10 km
Mounting standard	VESA 100 x 100, 75 x 75
Voltage insulation	...	≥ 21 kV / mm	---
Package capacity	...	2 x 250 ml
Connector type	Universal
Application	Visual localization of the fiber damage
Screen size range	17 " ... 32 "
Bearing capacity	9 kg
Operation mode	• continuous • pulsating light (pulsation frequency: 2 Hz)
Color	Black
Resolution	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	...
Tilt adjustment	-45 ° ... 45 °
Horizontal rotation	-90 ° ... 90 °
Rotation in the plane of the screen	360 °
Operation temp	...	-60 °C ... 200 °C
Main features	<ul style="list-style-type: none"> • The universal connector allows to connect all optical connectors of 2.5 mm standard, eg SC/FC/ST • Universal connector allows to test any fiber optic installation • The device works with both single-mode and multi-mode fibers • Low battery indicator • Backup time : ≤ 60 h • Water-resistant, solid construction • Mounted shield protects unused socket against dust • Small dimensions 	<ul style="list-style-type: none"> • Application : The product is dedicated to protecting electrical connections, • "Index of Protection" IP68, • There are scoops on the containers to control the amount of each ingredient, • Color : Blue 	Mount tube length 39.5 cm	...	<ul style="list-style-type: none"> • Magnetic tip • High-quality chrome-vanadium steel bar protects against corrosion and reduces the chance of tip breakage • Large handle offers optimal torque
Material	Plastic
Operation modes	Main and sub streams may be in any configuration Firmware 2.460.0000.14.R, build : 2017-07-20 • Main stream : 1920 x 1080, 1280 x 960, 1280 x 720 • Sub stream 1 : 704 x 576, 352 x 288 • Sub stream 2 : 1920 x 1080, 1280 x 720, 704 x 576, 352 x 288	...
Lens	---	...
View angle	---	...
Min. illumination	---	...
S/N ratio	> 50 dB	...
Audio	<ul style="list-style-type: none"> • External microphone input • Audio output • Bi-directional audio streaming support • Audio detection 	...
RS-485 interface	---	...
RS-232 interface	✓	...
Bitrate	24 ... 9472 kbps - H.264 14 ... 5632 kbps - H.265	...
Main stream frame rate	25 fps @ 1920 x 1080	...
Network protocols	HTTP, HTTPS, IPv4/IPv6, TCP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, UPnP, NTP, QoS, Bonjour, IEEE 802.1x, Multicast, ICMP, IGMP, SNMP	...
ONVIF	16.12	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Network interface	10/100 Base-T (RJ-45)	...
Alarm inputs / outputs	2 / 2	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile phones support	Port 37777 • Android: Free application DMSS • iOS (iPhone): Free application DMSS	...
Default admin user / password	admin / -	...
Default IP address	192.168.1.108	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...
Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Memory card slot	Micro SD memory cards up to 128GB support (possible local recording)	...
Power supply	2 x 1.5 V - Battery type LR6 (AA) (not included)	• 12 V DC / 580 mA, • PoE (802.3af)	...
Power consumption	< 7 W	...
Main features	• BLC - Back Light Compensation • HLC - High Light Compensation (spot) • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • Configurable Privacy Zones • IVS analysis - crossing the line (tripwire), intrusion, abandoned/missing object, face detection	...
Length of the cable	-	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.046 kg - Without batteries	0.6 kg (total)	2.1 kg	0.21 kg	0.035 kg
Dimensions	Ø 30 x 180 mm	75 x 81 x 161 mm	507 x 308 x 117 mm	110 x 83 x 24 mm	Ø 25 x 155 mm
Supported languages	English	...
Manufacturer / Brand	TriBrer	RayTech	BRATECK	DAHUA	STANLEY
Guarantee	2 years	2 years	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00