





	IP SPEED DOME CAMERA OUTDOOR DS-2DE4425IW-DE(T5) ACUSENSE 3.7 Mpx 4.8 ... 120 mm Hikvision	ELECTRIC CABLE DY-2.5-BK/750V	POLE MOUNT USH-S4	POLE MOUNT USH-S3
				
	897.39 EUR 897.39 EUR	0.43 EUR 0.43 EUR	17.43 EUR 17.43 EUR	26.40 EUR 26.40 EUR
Standard	TCP/IP
Support	SH-567/426/369	SH-750/595/322
Material	Magnelis - carbon steel, coated with a zinc-aluminum-magnesium alloy	Magnelis - carbon steel, coated with a zinc-aluminum-magnesium alloy
Sensor	1/2.8 " Progressive Scan CMOS
Number of fastening elements	2	3
Matrix size	4 Mpx
Plate thickness	2 mm	2 mm
In section	...	100 m . Price for 1m when buying a whole roll
Inner conductor	...	2.5 mm ² - Cu wire
Mounting holes distance	• 165 mm, • 510 mm	• 165 mm, • 510 mm
Rated voltage	...	450 / 750 V
Main features	The mounting with the steel strips (not included)	The mounting with the steel strips (not included)
Outer coating	...	Ø 3.3 mm - PVC
Coating color	...	Black
Resolution	2560 x 1440 3.7 Mpx , 1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens	4.8 ... 120 mm
View angle	• 55 ° ... 2.4 ° (manufacturer data) • 51 ° ... 4.3 ° (our tests result)
Optical zoom	x 25
Digital zoom	x 16
Range of IR illumination	100 m
S/N ratio	> 52 dB
Video output	—
Preset rotation speed	80 °/s
Rotation speed (manual control)	0.1 °/s ... 80 °/s (horizontal) 0.1 °/s ... 80 °/s (vertical)
Horizontal rotation range	360 ° - continuous
Vertical rotation range	-15 ° ... 90 °
RS-485 interface	—
Number of presets	300
Horizontal scan	✓
Route settings	8
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	1 / 1
Audio	• External microphone input • Audio output • Audio detection • Bi-directional audio streaming support • Noise reduction
Main stream frame rate	25 fps @ 3.7 Mpx
Network interface	10/100 Base-TX (RJ-45)
Network protocols	IPv4/IPv6, HTTP, HTTPS, IEEE 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour, WebSocket, WebSockets
WEB Server	Built-in, NVR compliance
Max. number of on-line users	20
ONVIF	✓

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default admin user / password	admin / - The administrator password should be set at the first start
Default IP address	192.168.1.64
Web browser access ports	80
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	8000
Port ONVIF	80
RTSP URL	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • EIS - Electronic Image Stabilization • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • Intelligent 3D Positioning System • ICR - Movable InfraRed filter • Configurable Privacy Zones - 24 • Motion Detection • Sharpness - sharper image outlines • Configurable: brightness, contrast, saturation • AGC - Automatic Gain Control • Day/Night mode (color/b&w/auto) • Auto White Balance • Parking action - this function enables to locate the camera to specific position automatically if operator doesn't operate the controller for some time • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, classification of people and vehicles, abandoned/missing object, face detection - advanced face capture features - detection of up to 5 faces simultaneously
Power supply	• PoE (802.3at), • 12 V DC / 1.5 A (power adapter included)
Power consumption	≤ 18 W
Housing	Speed Dome, Metal + Plastic
Color	White + Black
Operation temp	-30 °C ... 65 °C
"Index of Protection"	IP66
Weight	• 2.29 kg (without bracket) • 2.95 kg (with bracket)	...	0.97 kg	1.46 kg
Dimensions	• Ø 165 x 290 mm (without bracket) • 245 x 165 x 240 mm (with bracket)
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Vietnamese, Italian
Manufacturer / Brand	Hikvision
SAP Code	327000240
Guarantee	3 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00