



	<a href="#">SWITCH POE DS-3E1310HP-EI 8-PORT Hikvision</a>	<a href="#">POWER DISTRIBUTION UNIT PR-1.5M-3G- SW/USB/W (3 OUTLETS + 2 USB) 1.3 m</a>
		
	159.62 EUR 159.62 EUR	8.00 EUR 8.00 EUR
Rated voltage	...	220 ... 240 V AC / 50 Hz
Total maximal current	...	10 A
Maximal total load	...	2500 W
Number of outlets	...	<ul style="list-style-type: none"> <li>• 3 grounded outlets 10A/250V CEE 7/5,</li> <li>• 2 USB ports 2.1A/5V</li> </ul>
Fuse	...	—
Switch	...	✓
Wire gauge	...	3 x 1.5 mm <sup>2</sup>
Length of the cable	...	1.3 m
LAN ports	<ul style="list-style-type: none"> <li>• 8 x RJ45 10/100 Base-TX ( 2 x Hi-PoE (802.3af/at/bt) + 6 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 10/100/1000 Base-TX - Uplink</li> </ul>	...
Color	...	White
Transmission speed	<ul style="list-style-type: none"> <li>• 10 / 100 Mbps - 8 LAN &amp; PoE ports,</li> <li>• 10 / 100 / 1000 Mbps - 2 Uplink ports</li> </ul>	...
Maximal output power	<ul style="list-style-type: none"> <li>• 90 W / port Hi-PoE / PoE 802.3bt - 1, 2 ports</li> <li>• 30 W / port PoE 802.3af/at - 3 ... 8 ports</li> </ul>	...
Maximal total power	110 W	...
MAC addresses table	16k	...
Management	—	...
Default IP address	192.168.1.64	...
Default admin user / password	admin / -	...
Operation modes	<ul style="list-style-type: none"> <li>• Extend On : 300 m, 10 Mbps @ UTP cat. 5e, 6</li> <li>• Extend Off : 100 m, 100 Mbps @ UTP cat. 5e, 6</li> </ul>	...

Main features	<ul style="list-style-type: none"> <li>• The device supports 8-pin power supply</li> <li>• Configuration and management from the iVMS-4200 application</li> <li>• Remote update of software</li> <li>• View topology and network status</li> <li>• Data Flow Control</li> <li>• Alarm notifications</li> <li>• Possibility to mount to the wall</li> </ul>	...
LED diodes	Power, Link/Act, PoE, PoE Max, 9 Uplink, 10 Uplink	...
Certificates	CE	...
Housing	Desktop, Metal	Plastic
Protections	Overvoltage 6 kV - PoE ports	...
Power supply	54 V DC / 2.22 A (power adapter included)	...
Operation temp	-10 °C ... 55 °C	...
Weight	0.54 kg	0.32 kg
Dimensions	218 x 103 x 28 mm	202 x 49 x 40 mm
Manufacturer / Brand	Hikvision	...
SAP Code	301802043	...
Guarantee	3 years	2 years