



	<a href="#">POWER DISTRIBUTION UNIT OR-AE-13144 (4 OUTLETS + 2 USB) ORNO</a>	<a href="#">SOLAR CHARGE CONTROLLER SCC-100A-PWM-LCD-M2</a>
		
	17.52 EUR 17.52 EUR	45.89 EUR 45.89 EUR
Regulation Type	...	PWM
Rated voltage	230 V AC / 50 Hz	12 / 24 / 36 / 48 / 60 V
Total maximal current	10 A	...
Rated current	...	100 A
Maximal total load	2300 W	...
Number of outlets	<ul style="list-style-type: none"> <li>• 4 grounded outlets 10A/250V,</li> <li>• 2 USB ports 2.1A/5V</li> </ul>	...
Switch	—	...
Length of the cable	1.4 m	...
Housing	Plastic	...
Color	White + Gray	...
Permitted voltage range	...	max. 18 V for 12 V battery - The range of the highest operating voltage of a set of panels connected to one input of the controller max. 36 V for 24 V battery - The range of the highest operating voltage of a set of panels connected to one input of the controller max. 54 V for 36 V battery - The range of the highest operating voltage of a set of panels connected to one input of the controller max. 72 V for 48 V battery - The range of the highest operating voltage of a set of panels connected to one input of the controller max. 90 V for 60 V battery - The range of the highest operating voltage of a set of panels connected to one input of the controller
Battery charging current	...	max. 100 A
Load Current	...	max. 30 A
Manufacturer / Brand	ORNO	...

Output voltage	...	<ul style="list-style-type: none"> <li>• Equal to the voltage at the battery terminals - Cable terminals,</li> <li>• 5 V DC - USB sockets</li> </ul>
Main features	...	<ul style="list-style-type: none"> <li>• The device is designed to charge AGM and gel batteries only,</li> <li>• LCD display,</li> <li>• 2 x USB socket - Power output</li> </ul>
Weight	0.35 kg	0.3 kg
Dimensions	94 x 78 x 78 mm	169 x 94 x 40 mm
Guarantee	2 years	2 years