



	<a href="#">WIRELESS MAGNETIC CONTACT ATLO-KN1W-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">IP CAMERA IPC2125LE-ADF28KM-G - 5 Mpx 2.8 mm UNIVIEW</a>
		
	8.04 EUR 8.04 EUR	180.10 EUR 180.10 EUR
Standard	...	TCP/IP
Support	Tuya Smart	...
Sensor	...	1/2.7 " Progressive Scan CMOS
Detection	Opening the door or window	...
Matrix size	...	5 Mpx
Break distance	≥ 15 mm	...
Alarm signaling	Signal to the Tuya Smart mobile application	...
Frequency range	2.4 GHz WiFi - IEEE 802.11 b/g/n	...
Radio communication range	The range limited only by the availability of the Wi-Fi network	...
Alarm inputs	—	...
Battery	2 x 1.5V, type AAA/LR03 battery (included)	...
Current consumption	max. 55 mA	...
Main features	Low battery level alarm ≤ 2.2 V	...
Resolution	...	2880 x 1620 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p
Lens	...	2.8 mm
View angle	...	• 113 ° (manufacturer data) • 104 ° (our tests result)
Range of IR illumination	...	50 m
Operation temp	-10 °C ... 50 °C	...
S/N ratio	...	> 52 dB
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	...	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	• Microphone built-in • Audio transmission via network • Audio detection

Main stream frame rate	...	25 fps @ 5 Mpx
Network interface	...	10/100 Base-T (RJ-45)
Network protocols	...	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL / TLS, IEEE 802.1x, SNMP
WEB Server	...	Built-in
Max. number of on-line users	...	32
ONVIF	...	✓
Mobile phones support	It is possible to operate via the Wi-Fi network from the mobile application on the iOS, Android systems : <ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EZView</a></li> <li>• iOS (iPhone): Free application <a href="#">EZView</a></li> </ul>
Default IP address	...	DHCP or 192.168.1.13
Default admin user / password	...	admin / 123456
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream

Main features	...	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Mirror - Mirror image</li> <li>• Privacy zones - max. 4</li> <li>• Motion detection with human/vehicle silhouette recognition</li> <li>• Sharpness - sharper image outlines</li> <li>• Intelligent image analysis : intrusion, crossing the line (tripwire)</li> </ul>
Power supply	...	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 500 mA</li> </ul>
Power consumption	...	≤ 6 W
Housing	...	Compact, Metal + Plastic
Color	White	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	<ul style="list-style-type: none"> <li>• 0.018 kg - Reed switch</li> <li>• 0.01 kg - Magnet</li> </ul>	0.45 kg
Dimensions	<ul style="list-style-type: none"> <li>• Reed switch : 25 x 70 x 21 mm</li> <li>• Magnet : 15 x 40 x 18 mm</li> </ul>	190 73 x 71 mm
Supported languages	...	Polish, English, Czech, Spanish, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	...	UNIVIEW
Guarantee	2 years	3 years