




	IP CAMERA DS-2CD1047G2H-LIU(2.8MM) ColorVu - 3.7 Mpx Hikvision	ELECTRIC CABLE DY-2.5- RD/750V	BLANK MODULE SANTRA/4170-19/EPN Elektro-Plast
			
	288.07 CAD 288.07 CAD	0.64 CAD 0.64 CAD	2.80 CAD 2.80 CAD
Application	Santra product series
Standard	IP
Material	Plastic (ABS)
In section	...	100 m . Price for 1m when buying a whole roll	...
Inner conductor	...	2.5 mm ² - Cu wire	...
Rated voltage	...	450 / 750 V	...
Resolution	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Outer coating	...	Ø 3.3 mm - PVC	...
Sensor	1/3 " Progressive Scan CMOS
Coating color	...	Red	...
Lens	2.8 mm
View angle	115 °
White light LED illuminator range	30 m
Range of IR illumination	30 m
Memory card slot	—
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	—
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Audio transmission via network • Compliance with the AAC standard
Main stream frame rate	20 fps @ 3.7 Mpx
Interface	10/100 Base-T (RJ-45)
WEB Server	Built-in
Max. number of on-line users	6
ONVIF	—

Main features	<ul style="list-style-type: none"> • Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • SVC (Scalable Video Coding) - technology enabling the transfer of several sub-streams of different quality within one stream • Possibility to change the resolution, quality and bit rate • Horizontal mirror image • Smart motion detection (with recognizing people and vehicles) • Configurable Privacy Zones • Sharpness - sharper image outlines • video tampering • Filtering of false alarms based on the recognition of persons and vehicles
Mobile phones support	<ul style="list-style-type: none"> • Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default IP address	192.168.1.64
Default admin user / password	admin / - The administrator password should be set at the first start
Web browser access ports	80
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	8000
Port ONVIF	80
RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ <ul style="list-style-type: none"> • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 500 mA
Power consumption	<ul style="list-style-type: none"> • ≤ 7.5 W @ PoE • ≤ 6 W @ 12 V DC
Housing	Compact, Metal + Plastic
Color	White	...	Black
"Index of Protection"	IP67
Mechanical protection class	—
Operation temp	-30 °C ... 60 °C
Weight	0.3 kg	...	0.044 kg
Dimensions	Ø 70 x 173 mm	...	75 x 75 x 35 mm
Supported languages	English, Ukrainian
Manufacturer / Brand	Hikvision	...	Elektro-Plast Nasielsk
SAP Code	311325490
Guarantee	3 years	2 years	7 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00