



	IP CAMERA F4C-PV Wi-Fi, Smart Dual Light Active Deterrence - 3.7 Mpx 2.8 mm DAHUA	HDD ENCLOSURE Y-3035 UNITEK
		
	45.38 EUR 45.38 EUR	31.61 EUR 31.61 EUR
Standard	IP	...
Supported hard drives	...	1 x SATA III, 2.5 " / 3.5 "
Outputs	...	1 x USB 3.1, max. 5 Gb/s
Operation state indication	...	LED diodes
Resolution	2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...
Sensor	1/3 " Progressive Scan CMOS	...
Lens	2.8 mm	...
View angle	98 °	...
Range of IR illumination	30 m	...
White light LED illuminator range	30 m	...
S/N ratio	> 56 dB	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Image compression method	H.265+ / H.265 / H.264+ / H.264	...
Alarm inputs / outputs	—	...
Audio	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in, • Bi-directional audio streaming support • Audio output • Audio detection 	...
Main stream frame rate	25 fps @ 4 Mpx	...
Network interface	<ul style="list-style-type: none"> • Wi-Fi - IEEE 802.11 b/g/n, 2.4 GHz, • 10/100 Base-T (RJ-45) 	...
WEB Server	Built-in	...
Max. number of on-line users	6	...
ONVIF	✓	...
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS 	...
Default IP address	192.168.1.108	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 37777	...
PC client access ports	37777	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile client access ports	37777	...
Port ONVIF	80	...
RTSP URL	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream	...
Main features	<ul style="list-style-type: none"> • Active deterrence function • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Image rotation and mirror • Motion Detection - max. 4 configurable zones - Human detection • Privacy zones - max. 4 	...
Power supply	12 V DC / 550 mA	12 V DC / 2 A (power adapter included)
Power consumption	≤ 6.6 W @ 12 V DC	...
Housing	Compact - Plastic	Desktop, Plastic
Color	White + Black	...
"Index of Protection"	IP67	...
Vandal-proof	—	...
Operation temp	-40 °C ... 60 °C	...
Weight	0.25 kg	0.2 kg
Dimensions	131 x 78 x 97 mm	183 x 117 x 35 mm
Supported languages	Polish, English	...
Manufacturer / Brand	DAHUA	UNITEK
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00