



| | | | |
|---------------------------------|--|---|---|
| | SWITCH POE CS4010-8GT-110 8-PORT DAHUA | BATTERY AKU- AAA-950/GC*P4 1.2 V Ni-MH HR03, AAA Green Cell | AHD, HD-CVI, HD-TVI CAMERA APTI- H50PV21-28W 2Mpx / 5Mpx 2.8 mm |
| |  |  |  |
| | 290.36 USD 290.36 USD | 5.87 USD 5.87 USD | 24.80 USD 24.80 USD |
| Standard | ... | ... | AHD, HD-CVI, HD-TVI |
| In package | ... | 4 pcs The price for package | ... |
| Sensor | ... | ... | 1/3 " Progressive Scan CMOS |
| Rated voltage | ... | 1.2 V | ... |
| Matrix size | ... | ... | 5 Mpx |
| Battery capacity | ... | 950 mAh | ... |
| Battery type | ... | Ni-MH | ... |
| LAN ports | <ul style="list-style-type: none"> • 8 x RJ45 10/100/1000 Base-T (1 x Hi-PoE (802.3bt) + 7 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink | ... | ... |
| Size | ... | HR03, AAA | ... |
| Transmission speed | <ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 8 LAN & PoE ports, • 10 / 100 / 1000 : 2 Uplink ports | ... | ... |
| Maximal output power | <ul style="list-style-type: none"> • 90 W / port Hi-PoE / PoE 802.3bt - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 8 ports | ... | ... |
| Maximal total power | 110 W | ... | ... |
| MAC addresses table | 8k | ... | ... |
| Resolution | ... | ... | <ul style="list-style-type: none"> • 2592 x 1944 - 5 Mpx @ AHD, HD-TVI, • 2560 x 1440 - 3.7 Mpx @ AHD, HD-TVI, HD-CVI, • 1920 x 1080 - 1080p @ AHD, HD-CVI, HD-TVI |
| Management | ✓ | ... | ... |
| Range of IR illumination | ... | ... | 20 m |
| IR illuminator power adjustment | ... | ... | Automatic |
| Lens | ... | ... | 2.8 mm |
| Operation modes | Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6 | ... | ... |

| | | | |
|-----------------------|---|-----|---|
| View angle | ... | ... | <ul style="list-style-type: none"> • 89 ° (manufacturer data) • 83 ° (our tests result) |
| LED diodes | Power, System, PoE, Link/Act | ... | ... |
| Video output | ... | ... | 1 Vpp 75 Ω, AHD, HD-CVI, HD-TVI - selectable by switch |
| Main features | ... | ... | <ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • BLC - Back Light Compensation • Sharpness - sharper image outlines • Auto White Balance |
| OSD menu | ... | ... | OSD menu available via recorder |
| Main features | <ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Loop Protection • Compliance with the LLDP protocol • Spanning Tree STP/RSTP • Port Based VLAN : 32 • Data Flow Control (802.3x) • DHCP client • RESET button • Possibility to mount to the wall | ... | ... |
| Certificates | CE | ... | ... |
| Color | ... | ... | White |
| "Index of Protection" | ... | ... | — |
| Vandal-proof | ... | ... | — |

| | | | |
|----------------------|---|------------|--|
| Operation temp | ... | ... | -20 °C ... 60 °C |
| Protections | <ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV | ... | ... |
| Housing | Desktop, Metal | ... | Dome - Plastic |
| Power supply | 54 V DC / 2.22 A (power adapter included) | ... | 12 V DC / 180 mA |
| Power consumption | max. 110 W | ... | ≤ 2.2 W |
| Operation temp | -10 °C ... 55 °C | ... | ... |
| Supported languages | ... | ... | Polish, English, French, Spanish, Portuguese, Russian, Italian |
| Weight | 0.52 kg | 0.012 kg | 0.11 kg |
| Dimensions | 190 x 106 x 30 mm | ... | Ø 84 x 69 mm |
| Manufacturer / Brand | DAHUA | Green Cell | APTI |
| Guarantee | 3 years | 2 years | 2 years |