

	AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE16D8T- ITF(2.8mm) - 1080p Hikvision	POWER DISTRIBUTION UNIT AK-SP-05A AKYGA
		
	886.15 NOK 886.15 NOK	103.70 NOK 103.70 NOK
Rated voltage	...	230 V AC / 50 Hz
Total maximal current	...	10 A
Maximal total load	...	2500 W
Standard	AHD, HD-CVI, HD-TVI, PAL	...
Response time	...	< 25 ns
Sensor	Progressive Scan CMOS	...
Number of outlets	...	5 grounded outlets 10A/250V
Matrix size	2.1 Mpx	...
Automatic delayed fuse	...	10 A / 250 V
Resolution	1920 x 1080 - 1080p	...
Range of IR illumination	30 m	...
Nominal voltage of surge suppressor	...	250 V / 50 Hz
IR illuminator power adjustment	Automatic	...
Lens	2.8 mm	...
DC filter to eliminate interferences	...	RFI ≤ 10 dB
Maximum stroke current	...	4.5 kA
Maximum energy absorption	...	150 J
Switch	...	with light indication
View angle	<ul style="list-style-type: none"> • 104 ° (manufacturer data) • 97 ° (our tests result) 	...
Length of the cable	...	1.8 m
Operation temp	...	5 °C ... 50 °C
Video output	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / PAL, BNC socket	...

Main features	<ul style="list-style-type: none"> • WDR - 130 dB - Wide Dynamic Range • 2D-DNR / 3D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • Privacy zones - max. 4 • Motion Detection - max. 4 zones • ICR - Movable InfraRed filter • Mirror - Mirror image • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • Sharpness - sharper image outlines 	...
OSD menu	OSD menu available via Hikvision HD-TVI recorder	...
Power supply	12 V DC / 280 mA	...
Power consumption	≤ 3.4 W	...
Housing	Compact, Metal	Plastic (ABS)
Color	White + Black	Black
"Index of Protection"	IP67	...
Operation temp	-40 °C ... 60 °C	...
Weight	0.34 kg	0.306 kg
Dimensions	Ø 70 x 163 mm	305 x 50 x 40 mm
Supported languages	English	...
Manufacturer / Brand	Hikvision	AKYGA
SAP Code	300511199	...
Guarantee	3 years	2 years