

	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE16H0T-ITF(2.8MM)(C) - 5 Mpx Hikvision</a>	<a href="#">SMART PROXIMITY ACTION TRIGGER PROXIBOX/BLEBOX Wi-Fi, 12 ... 24 V DC</a>
		
	68.01 EUR 68.01 EUR	25.08 EUR 25.08 EUR
Application	...	Non-contact switching on and off, controlling devices, triggering actions
Rated voltage	...	12 ... 24 V DC
Standard	AHD / HD-CVI / HD-TVI / PAL	...
Maximal total load	...	—
Sensor	Progressive Scan CMOS	...
Total maximal current	...	—
Matrix size	5 Mpx	...
Number of inputs	...	0
Number of outputs	...	0
Connector type	...	screw terminals (power)
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11g
Mobile phones support	...	<ul style="list-style-type: none"> <li>• The <a href="#">wBox</a> free application on Android</li> <li>• The <a href="#">wBox</a> free application on iOS</li> </ul>
Resolution	<ul style="list-style-type: none"> <li>• 2560 x 1944 - 5 Mpx @ AHD / HD-TVI,</li> <li>• 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI</li> <li>• 1920 x 1080 @ HD-TVI</li> <li>• 960 x 576 @ PAL</li> </ul>	...
Lens	2.8 mm	...
View angle	<ul style="list-style-type: none"> <li>• 85 ° (manufacturer data)</li> <li>• 80 ° (our tests result)</li> </ul>	...
Range of IR illumination	30 m	...
IR illuminator power adjustment	Automatic	...

Main features	...	<ul style="list-style-type: none"> <li>• Multifunctional proximity sensor,</li> <li>• Distinguish between short and long signals,</li> <li>• remote access,</li> <li>• µWiFi technology support,</li> <li>• Possibility to hide the sensor,</li> <li>• Automatic calibration</li> <li>• LED indication</li> </ul>
Operation temp	...	-20 °C ... 50 °C
Video output	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / PAL, BNC socket	...
Audio	—	...
OSD menu	✓	...
Main features	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul>	...
Power supply	12 V DC / 360 mA	...
Power consumption	≤ 4.3 W	...
Housing	Compact, Metal	Plastic
Color	White + Black	Black
"Index of Protection"	IP67	IP20
Operation temp	-40 °C ... 60 °C	...
Weight	0.26 kg	0.026 kg
Dimensions	139 x 58 x 61 mm	53 x 40 x 18 mm
Supported languages	English	...
Manufacturer / Brand	Hikvision	BleBox
SAP Code	300512117	...
Guarantee	3 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00