



	<a href="#">TV OR MONITOR MOUNT BRATECK-PLB-CE344</a>	<a href="#">NVR TC-R3440 SPEC:I/B/N/V4.0 40 CHANNELS TIANDY</a>
		
	23.65 EUR 23.65 EUR	1008.55 EUR 1008.55 EUR
Standard	...	IP
Supported resolutions	...	max. 16 Mpx
Video outputs	...	1 pcs HDMI 4K 1 pcs VGA Video outputs are independent of each other
Mounting standard	VESA 75, 100, 200, 200x100, 400, 400x200	...
Audio support	...	40 Channels - Audio from cameras
Audio inputs	...	1 pcs
Screen size range	32 " ... 55 "	...
Audio outputs	...	1 pcs
Bearing capacity	50 kg	...
Image compression method	...	S+265 / H.265 / S+264 / H.264
Distance from mounting surface	(manufacturer data) : 1050 ... 1560 mm from ceiling Our tests results : 920 ... 1510 mm from ceiling	...
Supported hard drives	...	4 x 10 TB SATA
Color	Black	...
Recording modes	...	Manual, Motion Detection, Schedule
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Tilt adjustment	-15 ° ... 15 °	...
Horizontal rotation	360 °	...
Rotation in the plane of the screen	—	...
Searching and playback the records	...	<ul style="list-style-type: none"> <li>Records searching: by time and events type. Records playback: forward, backward, fast, slow</li> <li>Advanced searching (to the one second accuracy)</li> <li>Playback max. 16 cameras in the same time</li> </ul>
Network interface	...	2 x RJ-45 - 10 / 100 / 1000 Mbps
Network functions	...	Full support via network, Remote records copying, Web-Server built-in
ONVIF	...	✓
Bitrate	...	max. 400 Mbps

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.3
RTSP URL	...	rtsp://user:password@192.168.1.3:554/1/1 - Main stream rtsp://user:password@192.168.1.3:554/1/2 - Sub stream
Web browser access ports	...	80, 443, 3000, 3001, 3002, 23002
PC client access ports	...	3000, 3001
Mobile client access ports	...	3000, 3001
Mobile phones support	...	Port no.: 3000 or access by a cloud (P2P) • Android: Free application <a href="#">EasyLive Plus</a> • iOS (iPhone): Free application <a href="#">EasyLive Plus</a>
Access from PC	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>
Alarm inputs / outputs	...	16 / 4
Motion Detection	...	✓
Intelligent image analysis	...	—
USB	...	1 x USB 2.0 + 1 x USB 3.0
RS232	...	1 pcs
RS485	...	1 pcs
Mouse support	...	✓
IR remote controller in the set	...	—

Main features	...	<ul style="list-style-type: none"> <li>• Possibility of operation the disks in RAID JBOD/0/1/5/6/10 array</li> </ul> <p>Support for Intelligent Image Analysis function, available in TIANDY cameras :</p> <ul style="list-style-type: none"> <li>• crossing the line (tripwire)</li> <li>• double crossing the line</li> <li>• abandoned/missing object</li> <li>• detection of loitering in a given area</li> <li>• running</li> <li>• parking detection</li> <li>• heat map</li> <li>• scene changing</li> <li>• signal loss indication</li> <li>• License plate recognition</li> <li>• detection of persons on duty</li> <li>• detection of people gathering</li> <li>• Parking monitoring mode</li> <li>• protective helmet detection</li> <li>• people counting</li> <li>• advanced face capture features - (max 100 000 faces in the database)</li> </ul>
Power supply	...	12 V DC / 5 A (power adapter included)
Weight	5.7 kg	3.32 kg
Dimensions	1080 x 520 x 60 mm	440 x 355 x 76 mm
Supported languages	...	Polish, English, Albanian, Arabic, Spanish, Korean, Italian, Turkish, Russian, Thai, French, Dutch, Hebrew, Vietnamese, German, Ukrainian, Portuguese
Manufacturer / Brand	...	TIANDY
Guarantee	2 years	3 years