




	VIDEO SEPARATOR SV-1000/4-G	ACCESS CONTROLLER MODULE MC16-PAC-ST-2 ROGER	SINGLE-MODE PATCHCORD PC-2SC/2SC-3 3 m
			
	97.13 EUR 97.13 EUR	337.64 EUR 337.64 EUR	1.90 EUR 1.90 EUR
Connector type	SC/UPC <-> SC/UPC
Number of served transitions	...	2 (two-way)	...
Standard	CVBS - PAL / NTSC
Number of supported readers	...	8	...
Number of inputs	4 pcs BNC
Fiber optic type	9 / 125 μm
Number of outputs	4 pcs BNC
Total insertion loss	≤ 0.3 dB
Number of users	...	unlimited (purchase of the appropriate license required)	...
Input impedance	75 Ω
Output impedance	75 Ω
Number of media per ID	...	8 - Proximity card, PIN code, fingerprint, etc.	...
Galvanic (optical) isolation between signal inputs and outputs	1000 V peak
Length	3 m
Buffer memory	...	8 000 000 events buffer	...
Opto-isolation between power and signal inputs / outputs	1000 V peak
Number of access zones	...	4	...
Galvanic isolation between signal inputs	1000 V peak
Number of alarm zones	...	4	...
Galvanic isolation between signal outputs	1000 V peak
Battery backup support	...	12 V / 7 Ah	...
Gain adjustment	-5 ... +5 dB (adjust potentiometers are available after remove the cover)
Bandwidth	9 MHz / 1 Vpp
Transmission error	0.75 % (f=3.58MHz, Vin=1Vpp)

Communication	...	<ul style="list-style-type: none"> • Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface 	...
Assembly	To the wall
Main features	...	<ul style="list-style-type: none"> • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128 	<ul style="list-style-type: none"> • Made according to the requirements: G.652 D • PVC coating
Power supply	12 V DC / 300 mA	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	...
Operation temp	...	5 °C ... 40 °C	...
Permissible relative humidity	...	10 % ... 95 % (non-condensing)	...
Weight	0.310 kg	0.14 kg	...
Dimensions	213 x 36 x 93 mm	175 x 72 x 30 mm	...
Manufacturer / Brand	DELTA	ROGER	...
Guarantee	3 years	3 years	2 years