





	GLUE STICKS FOR SOLDERING GUNS MCE-434 12 PCS	WIRELESS VIDEO DOORPHONE ATLO-DBC52-TUYA Wi-Fi, Tuya Smart	POWER SUPPLY DISTRIBUTOR LZ-16/POL/R19	RFID PROXIMITY CARD ATLO-114N*P100
				
	42.53 SEK 42.53 SEK	1069.25 SEK 1069.25 SEK	441.08 SEK 441.08 SEK	517.52 SEK 517.52 SEK
Packaging	12 pcs
Number of power outputs	16 (2 x 8 outputs)	...
Sensor	...	SmartSens CMOS - 2 Mpx
Number of power inputs	2 (one per each 8-outputs terminal)	...
Dimensions of the sticks	Ø 11 x 150 mm
In package	100 pcs The price for package
Resolution	...	1920 x 1080 px - 1080p
Maximal power voltage	24 V DC (typical 12V)	...
Standard	Unique EM 125kHz
Maximal power supply current	6 A (for single terminal)	...
Compatibility	EM4100/4102
Lens	...	2.0 mm F1.2
Max. output current for single output	0.75 A	...
Possibility of programming the serial number (ID)	—
View angle	...	140 °
Ability to write to internal memory	—
Serial Number overprint	✓
Protection type	16 x 0.75 A - Polymer fuse	...
IR illuminator	...	5 ... 10 m
LED illuminator	...	—
proximity reader built-in	...	Unique EM 125kHz
Power connectors type	Input : Cable terminals Output : Cable terminals	...
Wireless transmission range	...	The range limited only by the availability of the Wi-Fi network
Wi-Fi standard	...	2.4 GHz IEEE 802.11 b/g/n
Permissible relative humidity	< 95 %	...
Main features	<ul style="list-style-type: none"> • Universal sticks for glue guns • A wide range of applications 	<ul style="list-style-type: none"> • Serial Number Format : 8H10D + WEG24A, • Range : ~ 15 cm, • The TK-4100 chip
Housing type	Rack 19"	...
Network interface	...	<ul style="list-style-type: none"> • 10/100 Mbps Fast Ethernet, RJ-45 socket • 2.4 GHz Wi-Fi

Mobile phones support	...	The Tuya Smart free application on Android The Tuya Smart free application on iOS
Image compression method	...	H.265 / H.264
Supported audio formats	...	G.711
Main features	...	<ul style="list-style-type: none"> • ATLO-DBC5/CHIME wireless support • Possibility of expansion with an additional ATLO-DBC5/RELAY wireless relay • Micro SD memory cards up to 256GB support (possible local recording) • Various record modes - users can choose time range for recording during day and set the specific recording mode: recording from motion detection, manual recording, schedule recording, • Motion Detection, • PIR detector, • Indoor proximity cards and key-fobs reader, • ICR - Movable InfraRed filter • Day/night mode, • Microphone built-in, • Speaker built-in, • Bidirectional communication, • Noise and echo reduction • Full support via network • 5 on-line users, • Possibility to work in cloud - you don't need to redirect the ports, • Video PUSH personal messaging - Motion Detection, • Video recording - Motion Detection, Doorbell button, • Automatic events notification via Email messages • Lock control - Relay output • Tamper protections • Google Home, Amazon Echo compliance
Mount	...	Surface-mounted
Power supply	...	<ul style="list-style-type: none"> • 12 V DC / 1 A (power adapter included) • 48 V PoE (802.3af)
Housing	...	Aluminum + Plastic (ABS)
Color	Transparent	Silver
"Index of Protection"	...	IP44



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Operation temp	...	-20 °C ... 55 °C	-50 °C ... 55 °C	...
Weight	0.014 kg (single element)	<ul style="list-style-type: none"> • 0.22 kg - Wireless Video Doorbell • 0.046 kg - rain cover 	0.3 kg	0.008 kg
Dimensions	...	<ul style="list-style-type: none"> • 141 x 87 x 25 mm - Wireless Video Doorbell • 147 x 94 x 40 mm - rain cover 	482 x 44 x 36 mm	86 x 54 x 2 mm
Manufacturer / Brand	DELTA	ATLO
Guarantee	2 years	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00