






	<a href="#">IP CAMERA TC-C35WO SPEC:15W/E/Y/2.8MM/V4.2 - 5 Mpx 2.8 TIANDY</a>	<a href="#">ACCESS CONTROL PANEL CPR32-SE-BRD_ROGER</a>	<a href="#">POE SWITCH_EXTENDER XPOE-4-11A-HS 4-PORT ATTE</a>	<a href="#">UTP / COAXIAL TRANSMITTER EOC-110KIT 2 PCS SET</a>	<a href="#">LABEL REMOVER ADHESIVE-REMOVER/200ML SPRAY 200 ml TESA</a>
					
	257.38 EUR 257.38 EUR	157.68 EUR 157.68 EUR	44.88 EUR 44.88 EUR	55.89 EUR 55.89 EUR	7.87 EUR 7.87 EUR
Standard	IP	...	...	...	...
Package	...	...	...	...	Spray 200 ml
Application	...	...	...	...	Removal of self-adhesive labels
Inputs	...	• 8 pcs - Mainboard inputs • max. 32	...	...	...
Transmission range	...	...	...	200 m @ RG6	...
LAN ports	...	...	• 1 x LAN + PoE IN - Port LAN 1, • 3 x LAN + PoE OUT - LAN2 ... LAN4 ports	1 pcs RJ45 1 pcs BNC socket	...
Outputs	...	• 4 pcs - Transistor outputs • 2 pcs - Relay outputs NO/NC	...	...	...
Management	...	...	—	...	...
Communication	...	• RS-485, • RACS (Roger)	...	...	...
LED diodes	...	...	Power, LAN	...	...
Transmission speed	...	...	10 / 100 Mbps	10 / 100 Mbps Half Duplex	...
Events memory	...	Non-volatile log buffer of the last 250 000 events	...	...	...
Resolution	2880 x 1620 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...	...	...	...
Maximal output power	...	...	• 40 W @ Passive PoE - LAN2 ... LAN4 ports • 13 W / 25 W @ PoE (802.3af/at) - LAN2 ... LAN4 ports	...	...
Sensor	1/2.7 " Progressive Scan CMOS	...	...	...	...
Lens	2.8	...	...	...	...
View angle	104 °	...	...	...	...
Range of IR illumination	50 m	...	...	...	...
White light LED illuminator range	15 m	...	...	...	...
Output load	...	• Transistor outputs : 1 A / 15 V DC • Relay outputs : REL1 - 1.5 A / 30 V DC REL2 - 5 A / 230 V AC	...	...	...
Memory card slot	Micro SD card support up to 512GB	...	...	...	...
Image compression method	S+265 / H.265 / H.264	...	...	...	...
Alarm inputs / outputs	1 / 1	...	...	...	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	...	<ul style="list-style-type: none"> <li>• Ability to block/unblock partition at a specified time, or as per access schedule,</li> <li>• Central management of the access control system,</li> <li>• Integration with the alarm system SATEL INTEGRA,</li> <li>• History of 250 000 events</li> <li>• Electrical protection of all inputs and outputs as well as communication buses</li> <li>• DIN, TS-35 rail mounting</li> </ul>	<ul style="list-style-type: none"> <li>• Possibility to power up to 3 PoE 802.3at/af or PASSIVE receivers</li> <li>• Possibility to connecting in cascade</li> <li>• The ability to turn off the power on selected PoE ports</li> <li>• The output PoE voltage is equal to the input voltage</li> <li>• Overvoltage protection</li> <li>• Short-circuit protection - LAN 1</li> </ul>	<ul style="list-style-type: none"> <li>• Plug &amp; Play and network devices</li> <li>• Full transparency for networks</li> </ul>	...
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Speaker built-in</li> <li>• Audio input</li> <li>• Audio output</li> <li>• Bi-directional audio streaming support</li> <li>• Audio transmission via network</li> </ul>	...	...	...	...
Battery backup support	...	✓	...	...	...
Main stream frame rate	<ul style="list-style-type: none"> <li>• 25 fps @ 5 Mpx</li> <li>• 50 fps @ 2 Mpx</li> </ul>	...	...	...	...
Operation temp	...	5 °C ... 40 °C	...	...	...
Interface	10/100 Base-TX (RJ-45)	...	...	...	...
WEB Server	Built-in	...	...	...	...
Max. number of on-line users	2	...	...	...	...
Permissible relative humidity	...	10 % ... 95 % (non-condensing)	...	...	...
ONVIF	✓	...	...	...	...
Mobile phones support	<ul style="list-style-type: none"> <li>Port no.: 3000 or access by a cloud (P2P)</li> <li>• Android: Free application <a href="#">EasyLive Plus</a></li> <li>• iOS (iPhone): Free application <a href="#">EasyLive Plus</a></li> </ul>	...	...	...	...
Access from PC	<ul style="list-style-type: none"> <li>Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a></li> </ul>	...	...	...	...
Default IP address	192.168.1.2	...	...	...	...
Default admin user / password	admin / - The administrator password should be set at the first start	...	...	...	...
Web browser access ports	80, 443, 3000, 3001, 3002, 23002	...	...	...	...
Mobile client access ports	3000, 3001	...	...	...	...
PC client access ports	3000, 3001	...	...	...	...
Port ONVIF	80	...	...	...	...
Intelligent image analysis	<ul style="list-style-type: none"> <li>• classification of people and vehicles</li> <li>• crossing the line (tripwire)</li> <li>• video tampering</li> </ul>	...	...	...	...

Main features	<ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Early Warning (EW) - combination of white light warning with audio signals</li> <li>• ICR - Movable InfraRed filter</li> <li>• Day/night mode</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Audio detection</li> </ul>	...	...	...	...
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 670 mA</li> </ul>	<ul style="list-style-type: none"> <li>• 24 V DC</li> <li>• 12 V DC</li> <li>• 18 V AC</li> </ul>	<ul style="list-style-type: none"> <li>• 44 ... 56 V DC - LAN 1,</li> <li>• 12 ... 56 V DC - LAN 2 ... LAN 4</li> </ul>	...	...
Power consumption	≤ 8 W	...	...	...	...
Housing	Compact - Metal	...	...	...	...
Color	White	...	...	...	...
"Index of Protection"	IP67	...	...	...	...
Mechanical protection class	—	...	...	...	...
Operation temp	-40 °C ... 65 °C	...	...	...	...
Weight	0.52 kg	0.12 kg	0.04 kg	0.055 kg (single element)	0.200 kg
Dimensions	170 x 71 x 71 mm	105 x 85 x 50 mm	94 x 41 x 18 mm	72 x 25 x 25 mm (single element)	Ø 53 x 173 mm
Supported languages	Polish, English, Spanish, Korean, Italian, Turkish, Russian, Thai, French, Dutch, Hebrew, Arabic, Vietnamese, German, Ukrainian, Portuguese, Albanian	...	...	...	...
Manufacturer / Brand	TIANDY	ROGER	ATTE	...	TESA
Guarantee	3 years	3 years	3 years	2 years	...