





	MAINS SOCKET TESTER WITH RCD CHECKING FUNCTION UT-07B-EU UNIT	CONNECTION BOX PHW-75X75/EPN IP67 Elektro-Plast	CABLE FOR SOLAR INSTALLATIONS H1Z2Z2-K-1X4.0/RD	ACCESS CONTROLLER ASC2202B-S DAHUA
				
	14.10 AUD 14.10 AUD	7.01 AUD 7.01 AUD	1.48 AUD 1.48 AUD	346.39 AUD 346.39 AUD
Number of served transitions	2 (one-way)
Support	DAHUA
Number of intakes	...	4 - Cable glands PG-16
Number of supported readers	4 pcs
Battery backup support	—
Cable diameter	...	10 ... 14 mm
Output lines	2 pcs - Relay
Inner conductor	4.0 mm ² - Stranded wire Cu - Tin-plated	...
Material	...	Non-halogen plastic
Rated voltage	230 V AC	...	600 V / 1000 V AC 1800 V DC	...
Communication	<ul style="list-style-type: none"> • RS-485, • Ethernet, • Wiegand
Color	...	Gray
"Index of Protection"	IP40	IP67
Outer coating	Ø 5.0 mm - Non-halogen plastic	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3at), • 12 V DC / 4 A

Main features	<ul style="list-style-type: none"> • RCD test (residual current device test) : ~ 30 mA • Phase conductor position test • Signaling a lack of grounding • Signaling phase failure • Signaling a lack of a neutral wire • Signaling of phase and ground swap • Signaling of phase and ground swap and a lack of grounding 	<ul style="list-style-type: none"> • Surface mount • Cover mounting with screws • The set includes a 5 x 4 mm² insert • Compliance with PN-EN 60670-1 standards 	<ul style="list-style-type: none"> • UV radiation resistance • Ozone resistance • Hydrolysis resistance • Resistant to oils and aggressive chemicals • Flame resistance (according to VDE 0482-332-2, DIN EN 60332-1) • The insulating layer is made of halogen-free material, which does not produce aggressive fumes during combustion • Increased mechanical strength of the outer coating • Expected lifetime : 25 years 	<ul style="list-style-type: none"> • 100000 indexed users • History of 500000 events • Remote programming from PC • Function of protection against multiple use of the same card for access (anti-passback) • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress • Possibility to mount on a wall, or on the DIN TS-35 rail
Coating color	Red	...
Default IP address	192.168.0.2
Default admin user / password	admin / - The administrator password should be set at the first start
Operation temp	0 °C ... 40 °C	-30 °C ... 60 °C
Permissible relative humidity	5 % ... 90 % (non-condensing)
Weight	0.08 kg	0.27 kg
Dimensions	65 x 65 x 72 mm	85 x 85 x 41 mm - External dimensions , 75 x 75 x 33 mm - Internal dimensions	...	155 x 116 x 50 mm
Manufacturer / Brand	UNI-T	Elektro-Plast	...	DAHUA
Guarantee	2 years	2 years	2 years	3 years