



	POE SWITCH / EXTENDER PFT1310 3-PORT	SWITCH POE IP-8-20-H 8-PORT ATTE
		
	20.80 USD 20.80 USD	327.92 USD 327.92 USD
LAN ports	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T + power input : PoE (802.3af/at), • 2 x RJ45 10/100 Base-T + PoE (802.3af) 	<ul style="list-style-type: none"> • 2 x RJ45 10/100/1000 Base-TX - Uplink • 8 x RJ45 10/100 Base-TX + PoE (802.3af/at) / Passive PoE
Management	—	—
LED diodes	LAN, PoE	Power, LAN
Transmission speed	10 / 100 Mbps	<ul style="list-style-type: none"> • 10 / 100 Mbps : 8 LAN & PoE ports • 10 / 100 / 1000 Mbps : 2 Port LAN
Power consumption	0.3 W	...
Maximal output power	<ul style="list-style-type: none"> • 15.4 W @ port PoE - First device • 3 W @ port PoE - Second device in cascade 	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 8 ports, • 30 W @ PoE (802.3at) - 1 ... 8 ports, • 15.4 W @ PoE (802.3af) - 1 ... 8 ports
Maximal total power	...	96 W
Range	100 m - Input 100 m - Output	...
Protections	Overvoltage	...
Housing	Plastic, DIN, TS-35 rail mounting	...
Operation temp. / Relative humidity	-30 ... 65 °C / 10 ... 90 %	...

Main features	<ul style="list-style-type: none"> • Possibility to connecting in cascade • The device can function as a LAN network and PoE power extender 	<ul style="list-style-type: none"> • Pin numbers for RJ-45 connector : 1/2, 3/6 - Wires to data transmission ; 4/5, 7/8 - Power supply • Possibility to connecting in cascade • Efficiency : 92 % @ 90 W • Built-in switching power supply : 48 V DC / 96 W • PSU thermal protection • Short-circuit protection • Overload protection • TAMPER switch indicating open the cover • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 8 ports • Electronic fuse independently for each PoE channel • The modular design streamlines service tasks and enables quick and easy system expansion • The raster system of module assembly facilitates the expansion of the device by further modules • Main cable entries on the back of the enclosure • "Index of Protection" : IP20
Power supply	PoE (802.3af/at)	180 ... 240 V AC - Built-in switching power supply
Weight	0.05 kg	4.33 kg
Dimensions	79 x 52 x 23 mm	400 x 450 x 140 mm
Manufacturer / Brand	...	ATTE
Guarantee	2 years	3 years