




	<a href="#">POE POWER ADAPTER POE-48/NX 24 W</a>	<a href="#">EXPANSION PLUG KS-14/10X100 KLIMAS</a>	<a href="#">COMPRESSION PLUG F/6.8- ZAC-PLAT</a>
			
	8.85 EUR 8.85 EUR	0.65 EUR 0.65 EUR	0.34 EUR 0.34 EUR
Standards	IEEE 802.3at	...	...
Connector type	...	...	"F" Plug
Attachment of connector elements	...	...	Compression mounting
Input voltage	100 V ... 240 V AC	...	...
Application	...	...	Coaxial cable
Output voltage	48 V DC	...	...
Number of inputs	1	...	...
Drilling diameter	...	14 mm	...
Expansion plug length	...	80 mm	...
Frequency range	...	...	0 GHz ... 3 GHz
Connector	2 x RJ-45 socket	...	...
VSWR	...	...	< 1.1
LED indicators	Power connection	...	...
Impedance	...	...	75 Ω
Output power	24 W	...	...
Screw dimensions	...	Ø 10 x 100 mm, SW-17	...
Return loss	...	...	30 dB
Wire mounting	...	...	—
Protections	<ul style="list-style-type: none"> <li>• Short-circuit</li> <li>• Overload</li> </ul>	...	...
Cable diameter	...	...	max. 6.8 mm
Housing	Plastic	...	...
Shielding at 1GHz	...	...	100 dB
Application	...	<ul style="list-style-type: none"> <li>• Concrete</li> <li>• Solid clay brick</li> <li>• Solid sand-lime brick</li> <li>• Natural stone</li> </ul>	...
Shield fastening	...	...	Compression mounting
Manufacturer / Brand	...	KLIMAS	...
Plastic bush	...	...	DuPont Delrin 527UV*
Material	...	<ul style="list-style-type: none"> <li>• Expansion plug, Polypropylene</li> <li>• Screw, Steel galvanized</li> </ul>	Brass (Nickel-platted)
Operation temp. / Relative humidity	0 °C ... 40 °C / 5 % ... 90 %	...	...
Bush	...	...	EPDM
Watertightness	...	...	✓

Example of application	...	...	Triset113
Main features	...	...	<ul style="list-style-type: none"> <li>• Wide frequency range</li> <li>• Watertightness of connector with cable connection</li> <li>• Resistance to corrosion - made of non-ferrous metals and highest-quality dielectric</li> <li>• Very low loss in the whole operating band</li> <li>• Perfect matching to the transmission line within the whole operating band</li> <li>• Properly compressed connection is highly resistant to break</li> <li>• Many patent-pending solutions</li> <li>• To crimp use the crimping tool ZAC/PCT / ZAC/TR-255</li> </ul>
Weight	0.200 kg	...	0.075 kg
Dimensions	85 x 44 x 30 mm	...	Ø 13 mm x 27 mm
Guarantee	2 years	2 years	2 years