



	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR DS-7108HQHI-K1(C)(S) 8 CHANNELS Hikvision	BATTERY 12V/9AH-MWP
		
	207.64 CAD 207.64 CAD	33.79 CAD 33.79 CAD
Battery capacity	...	9 Ah
Rated voltage	...	12 V
Battery charging current	...	max. 2.6 A
Battery type	...	Maintenance-free AGM (Absorbent Glass Mat) battery
Standard	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP	...
Connector	...	T2 type
Battery lifetime	...	> 12 years
Video inputs	8 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS	...
Video outputs	1 pcs HDMI 1 pcs VGA	...
Audio inputs	1 pcs CINCH, Coaxial audio - Audio from cameras	...
Audio outputs	1 pcs CINCH	...
Image compression method	H.265 Pro+ / H.265 Pro / H.265 / H.264+ / H.264	...
Image records resolutions	<ul style="list-style-type: none"> • HD-TVI : 4M-N - 1280 x 1440 , 3 Mpx - 1920 x 1536 - Channel 1 / 2 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 • AHD : 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 • HD-CVI : 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , • CVBS : 960H - 960 x 576 , • IP : max. 6 Mpx - 3072 x 2048 	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Recording speed adjustment	6 Mpx IP @ 1 ... 25 fps 4M-N @ 1 ... 15 fps 3 Mpx @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps D1 @ 1 ... 25 fps for each channel	...
Operation modes	8 x HD-TVI / AHD / HD-CVI / CVBS / IP + 4 x IP	...
Recording modes	Manual, Motion Detection, Schedule	...
Supported hard drives	1 x 6 TB SATA	...
External storage devices backup	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 8 cameras in the same time	...
Network interface	1 x RJ-45 - 10/100 Base-TX	...
Bitrate	32 ... 6144 kbps	...
Network functions	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters	...
Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect	...
Default admin user / password	admin / -	...
Default IP address	DHCP or 192.168.1.64	...
Web browser access ports	80	...
PC client access ports	554 RTSP, 8000	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream	...
Alarm inputs / outputs	—	...
PTZ control	Control compatible with coax HD-TVI Hikvision	...
Motion Detection	Split the screen into zones : 22 x 18 motion zones	...
USB	2 pcs USB 2.0	...
Mouse support	✓	...
IR remote controller in the set	—	...
Power supply	12 V DC / 1.5 A (power adapter included)	...
Color	White	...

Weight	0.5 kg	2.74 kg
Dimensions	210 x 200 x 48 mm	151 x 65 x 94 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian	...
Manufacturer / Brand	Hikvision	...
SAP Code	300226918	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00