





	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC- HDW1400TL-0280B - 3.7 Mpx 2.8 mm DAHUA	STAIRS LIGHTING TIMER OR-PRE-455 ORNO	COMPRESSION PLUG BNC- W/ZAC-RG-6/MSR
			
	78.68 EUR 78.68 EUR	29.32 EUR 29.32 EUR	0.78 EUR 0.78 EUR
Number of relay outputs	...	1 pcs NO	...
Standard	HD-CVI, HD-TVI, AHD, CVBS
Relay maximal load	...	16 A / 250 V AC (max)	...
Sensor	1/2.7 " CMOS
Connector type	BNC Straight plug
Matrix size	3.7 Mpx
Lighting time adjustment	...	1 s ... 10 minutes	...
Attachment of connector elements	Compression mounting
Impedance	75 Ω
Material	Brass (Nickel-plated)
Application	Coaxial cable
Assembly	...	DIN TS-35 rail	...
Wire mounting	Pressing
Operation temp	...	-20 °C ... 50 °C	...
Cable diameter	max. 8.0 mm
Shield fastening	Compression mounting
Watertightness	✓
Example of application	• RG6
Resolution	<ul style="list-style-type: none"> • AHD / HD-CVI / HD-TVI : 2560 x 1440 - 3.7 Mpx , • HD-CVI : 1920 x 1080 - 1080p , • CVBS 960 x 576 - 960H, PAL
Range of IR illumination	30 m
IR illuminator power adjustment	Automatic

Main features	...	<ul style="list-style-type: none"> • Smooth adjustment of the working time • Bistable operation controlled by the S control input 	<ul style="list-style-type: none"> • Wide frequency range • Very low loss in the whole operating band • Watertightness of connector with cable connection • Resistance to corrosion - made of non-ferrous metals and highest-quality dielectric • Perfect matching to the transmission line within the whole operating band • Properly compressed connection is highly resistant to break • Many patent-pending solutions • To crimp use the crimping tool HT-5082R
Lens	2.8 mm
View angle	<ul style="list-style-type: none"> • 97 ° (manufacturer data) • 94 ° (our tests result)
Video output	AHD / HD-CVI / HD-TVI / PAL, 1 V _{pp} / 75 Ω
Audio	—
Main features	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Privacy zones • Mirror - Mirror image • Sharpness - sharper image outlines
OSD menu	OSD menu available via DAHUA recorder
Power supply	12 V DC / 330 mA	230 V AC	...
Power consumption	≤ 4 W
Housing	Dome, Aluminum + Plastic
"Index of Protection"	IP67
Color	White
Vandal-proof	—
Operation temp	-40 °C ... 60 °C
Weight	0.22 kg	0.073 kg	0.015 kg

Dimensions	Ø 97 x 86 mm	97 x 17 x 64 mm	Ø 14.5 mm x 37 mm
Manufacturer / Brand	DAHUA	ORNO	...
Guarantee	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00