

	<a href="#">PLUG F/7.0-CFS</a>	<a href="#">WHOLE HOME WI-FI SYSTEM RG-M32(2PACK)</a> <a href="#">Wi-Fi 6, 2.4 GHz, 5 GHz, 800 Mbps + 2402 Mbps</a> <a href="#">REYEE</a>	<a href="#">ACCESS CONTROLLER WITH FACE RECOGNITION</a> <a href="#">DS-K1T341AM-S - 720p</a> <a href="#">Hikvision</a>
			
	0.50 AUD 0.50 AUD	482.39 AUD 482.39 AUD	777.03 AUD 777.03 AUD
Number of devices included	...	2 pcs	...
Sensor	...	...	CMOS
Connector type	"F" Straight plug	...	...
Matrix size	...	...	2 Mpx
Attachment of connector elements	Twisted-on	...	...
Shield fastening	Twisting-on	...	...
Resolution	...	...	1280 x 720 - 720p
Wire mounting	—	...	...
Application	Coaxial cable	...	...
Frequency range	...	• 2.4 GHz, • 5 GHz ,	...
Cards support	...	...	13.56 MHz S50
Cable diameter	max. 7.0 mm	...	...
Impedance	75 Ω	...	...
Face recognition distance	...	...	0.3 m ... 1.5 m
Material	Metal	...	...
Memory	...	...	• Memory of 1500 face templates • Memory of 1500 RFID cards • Non-volatile log buffer of the last 150 000 events
Example of application	• RG6 • HFEK • Triset113	...	...
Antenna type	...	4x4 MU-MIMO - built-in 4 pcs dual-band • 4 dBi @ 2.4 GHz • 4 dBi @ 5 GHz	...
Standard	...	...	TCP/IP
IR illuminator	...	...	—
Standards	...	IEEE 802.11ax Wi-Fi 6	...
LED illuminator	...	...	—
Video output	...	...	—
RS-485 interface	...	...	✓

Memory card slot	...	...	—
Baud rates	...	800 Mbps @ 2.4 GHz + 2402 Mbps @ 5 GHz	...
Alarm inputs / outputs	...	...	—
Audio	...	...	Speaker built-in
LAN ports	...	3 x 10 / 100 / 1000 Mbps - RJ45	...
Network interface	...	...	10/100/1000 Mbps (RJ-45)
WAN interface	...	1 x 10 / 100 / 1000 Mbps - RJ45	...
Network protocols	...	...	TCP/IP, ISUP, ISAPI
Port USB	...	—	...
WEB Server	...	...	Built-in
ONVIF	...	...	—
LED indicators	...	Power / System / Mesh, Signal indicator	...
Default admin user / password	...	...	admin / - The administrator password should be set at the first start
DDNS	...	—	...
Web browser access ports	...	...	80
DHCP server	...	✓	...
PC client access ports	...	...	port 8000
Firmware update	...	✓	...
Protections	...	<ul style="list-style-type: none"> <li>• WPA/WPA2</li> <li>• Black list</li> <li>• parental control</li> <li>• SSID hiding</li> <li>• Firewall</li> </ul>	...
Operation modes	...	<ul style="list-style-type: none"> <li>• Repeater</li> <li>• Router</li> <li>• Access Point</li> <li>• WISP</li> </ul>	...

Main features	...	...	<ul style="list-style-type: none"> <li>• 4.3 " capacitive touch screen</li> <li>• Mechanical tamper protection</li> <li>• WDR - Wide Dynamic Range</li> <li>• AI detection : Face recognition</li> <li>• Configuration and management from the iVMS-4200 application</li> <li>• Port USB</li> <li>• Recording of information about Time&amp;Attendance</li> <li>• Possibility to open the gate using a QR code</li> <li>• Door lock control output</li> <li>• Possibility to connect an exit button and a reed switch to control the door status</li> </ul>
Management interface	...	<ul style="list-style-type: none"> <li>• Configuration using the Ruijie Reyee application</li> <li>• Remote management</li> <li>• Web browser</li> </ul>	...
Mobile phones support	...	Android: Free application <a href="#">Ruijie Reyee</a> iOS (iPhone): Free application <a href="#">Ruijie Reyee</a>	...
Default IP address	...	192.168.110.1	192.168.1.64
Color	...	...	Black / Silver
"Index of Protection"	...	...	—
Operation temp	...	...	-30 °C ... 60 °C
Transmitter power	...	max. 20 dBm @ 2.4 GHz max. 27 dBm @ 5 GHz	...
Supported languages	...	...	English, German, French, Polish, Czech, Hungarian, Bulgarian, Serbian, Slovenian, Albanian
SAP Code	...	...	302917454

Main features	<ul style="list-style-type: none"> <li>• Wide frequency range</li> <li>• Corrosion resistance</li> </ul>	<ul style="list-style-type: none"> <li>• Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments</li> <li>• OFDMA</li> <li>• Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source</li> <li>• MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network</li> <li>• Load balance</li> <li>• WLAN : max. 6 x BSSID</li> <li>• IPv4/IPv6 - Static routing</li> <li>• PPPoE</li> <li>• IPTV</li> <li>• WMM support (QoS mechanism of the 802.11e standard)</li> <li>• VPN support : PPTP VPN Server / Client</li> <li>• Guest Network - a separate and secure network for guests</li> <li>• Support for Reyee Mesh technology</li> <li>• System logs</li> <li>• RESET button</li> <li>• MESH button</li> </ul>	...
Housing	...	Plastic	Metal
Power supply PoE	...	—	...
Power supply	...	12 V DC / 2.5 A (included)	12 V DC / 2 A (power adapter included)
Power consumption	...	max. 30 W	≤ 24 W
Operation temp	...	-10 °C ... 45 °C	...
Permissible relative humidity	...	5 % ... 95 % (non-condensing)	...
Weight	0.005 kg	0.66 kg (single element)	0.31 kg
Dimensions	Ø 11 mm x 19 mm	119 x 119 x 200 mm (single element)	173 x 83 x 23 mm (without bracket)
Manufacturer / Brand	...	RUIJIE / REYEE	Hikvision
Guarantee	2 years	3 years	3 years