




	<a href="#">ADAPTER AD-UTP 2x RJ45 / 1x RJ45</a>	<a href="#">RELAY MODULE AWZ-513</a>	<a href="#">WIRELESS TEMPERATURE DETECTOR ATLO-THD1- TUYA Wi-Fi, Tuya Smart</a>
			
	3.09 GBP 3.09 GBP	7.69 GBP 7.69 GBP	14.90 GBP 14.90 GBP
Support	...	...	Tuya Smart
Number of relay outputs	...	2 - Relays controlled by a single control input	...
Connectors type	<ul style="list-style-type: none"> <li>• 2 x RJ-45 shielded socket</li> <li>• 1 x RJ-45 plug - Shielded</li> </ul>	...	...
Detection	...	...	Temperature / relative humidity
Length of the cable	12 cm	...	...
Measurement range	...	...	-10 °C ... 55 °C
Measurement of humidity	...	...	0 % ... 99 %
Alarm signaling	...	...	<ul style="list-style-type: none"> <li>• Buzzer,</li> <li>• Signal to the Tuya Smart mobile application</li> </ul>
Relay maximal load	...	2 A (max), 30 V DC / 50 V AC (max)	...
Output	...	2 x NO/NC	...
Frequency range	...	...	2.4 GHz WiFi IEEE 802.11 b/g/n
Radio communication range	...	...	The range limited only by the availability of the Wi-Fi network
Mobile phones support	...	...	<p>It is possible to operate via the Wi-Fi network from the mobile application on the iOS, Android systems :</p> <ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>
Alarm inputs	...	...	—
Manufacturer / Brand	...	PULSAR	...
Power supply	...	10 ... 14 V DC	<ul style="list-style-type: none"> <li>• 2 x battery LR3 (AAA) 1.5 V (included)</li> <li>• micro USB socket 5 V / 2 A</li> </ul>
Current consumption	...	25 mA @ 12 V DC	max. 60 mA

Main features	...	<ul style="list-style-type: none"> <li>• LED indication</li> <li>• 2 x 5/20mm delayed fuse - 0.5 A, 2 A</li> </ul>	<ul style="list-style-type: none"> <li>• LCD display</li> <li>• Digital detector</li> <li>• Signal indicator</li> <li>• Battery charge indicator</li> <li>• Two programmable temperature thresholds (upper and lower)</li> <li>• Two programmable humidity thresholds (upper and lower)</li> <li>• Selectable measurement unit: °C / °F</li> <li>• Low battery level alarm <math>\leq</math> 2.2 V</li> <li>• Sound signaling : 55 dB</li> <li>• Wall mounting</li> </ul>
Color	...	...	White
Operation temp	...	-10 °C ... 50 °C	-10 °C ... 60 °C
Permissible relative humidity	...	...	max. 90 % (non-condensing)
Weight	0.04 kg	0.03 kg	0.05 kg
Dimensions	50 x 37 x 21 mm	70 x 43 x 24 mm	Ø 61 x 27 mm
Guarantee	2 years	2 years	2 years