



	<a href="#">EXTENSION CABLE PS-2X1.5-20M/ORANGE 20 m</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL VANDALPROOF CAMERA HAC-HDBW2241F-A-0280B-S2-DIP - 1080p 2.8 mm DAHUA</a>	<a href="#">VIDEO SEPARATOR WITH OPTO-ISOLATION SV-1000A STANDARD: AHD, HD-CVI</a>	<a href="#">OVERVOLTAGE LIMITER LE-412223 THREE-PHASE 2 TYPE LEGRAND</a>
				
	41.12 PLN 41.12 PLN	577.00 PLN 577.00 PLN	156.75 PLN 156.75 PLN	344.35 PLN 344.35 PLN
Length of the cable	20 m	...	...	...
Wire gauge	2 x 1.5 mm <sup>2</sup>	...	...	...
Device type	...	...	...	Overvoltage limiter, Three-phase
Standard	...	AHD, HD-CVI, HD-TVI, PAL	...	...
Sensor	...	Progressive Scan CMOS	...	...
Total maximal current	10 A	...	...	...
Rated voltage	230 V AC / 50 Hz	...	...	230 / 400 V AC, 50 / 60 Hz
Matrix size	...	2.1 Mpx	...	...
Standard	...	...	<ul style="list-style-type: none"> <li>• AHD - 4 Mpx</li> <li>• HD-CVI - 720p</li> <li>• CVBS - PAL / NTSC</li> </ul>	...
Maximal total load	2500 W	...	...	...
Number of inputs	...	...	1 pcs BNC	...
Number of outlets	1 x CEE 7/17	...	...	...
Maximal voltage	...	...	...	320 V AC, 50 / 60 Hz
Number of outputs	...	...	1 pcs BNC	...
Fuse	—	...	...	...
Input impedance	...	...	75 Ω	...
Switch	—	...	...	...
Output impedance	...	...	75 Ω	...
Class	...	...	...	2 type ( Class C )
Galvanic (optical) isolation between signal inputs and outputs	...	...	1000 V peak	...
Resolution	...	1920 x 1080 - 1080p , 960 x 576 - 960H, PAL	...	...
Opto-isolation between power and signal inputs / outputs	...	...	1000 V peak	...
Protection level Up L/PE, N/PE	...	...	...	1.2 kV @ 8/20 μs (T2)
Range of IR illumination	...	30 m	...	...
Nominal discharge current (L/PE, N/PE)	...	...	...	5 kA @ 8/20 μs (T2)
IR illuminator power adjustment	...	Automatic	...	...
Gain adjustment	...	...	-3 dB ... +3 dB	...
Lens	...	2.8 mm	...	...
Maximum stroke current (L/N, L/PE, N/PE)	...	...	...	20 kA @ 8/20 μs (T2)
Bandwidth	...	...	33 MHz / 1 Vpp	...
Operation state indication	...	...	...	✓
Connectors type	...	...	...	screw terminals

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

View angle	...	<ul style="list-style-type: none"> <li>• 109 ° (manufacturer data)</li> <li>• 101 ° (our tests result)</li> </ul>	...	...
S/N ratio	...	> 65 dB	...	...
Width in 17.5 mm modules	...	...	...	4
Video output	...	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω - selectable by switch	...	...
Audio	...	Microphone built-in - HD-CVI only	...	...
Main features	...	<ul style="list-style-type: none"> <li>• WDR - 130 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• ICR - Movable InfraRed filter</li> <li>• Day/night mode</li> <li>• Auto White Balance</li> <li>• AGC - Automatic Gain Control</li> <li>• Sharpness - sharper image outlines</li> <li>• Mirror - Mirror image</li> <li>• Privacy zones - max. 8</li> </ul>	...	...
OSD menu	...	OSD menu available via DAHUA recorder	...	...
Power supply	...	12 V DC / 225 mA	12 V DC / 90 mA	...
Power consumption	...	≤ 2.7 W	...	...
Housing	...	Dome, Metal	...	Plastic, DIN, TS-35 rail mounting
Color	Orange	White	...	...
Vandal-proof	...	IK10	...	...
"Index of Protection"	...	IP67	...	...
Operation temp	...	-40 °C ... 60 °C	...	...
Weight	1.5 kg	0.33 kg	0.088 kg	0.334 kg
Dimensions	...	Ø 106 x 51 mm	120 x 62 x 30 mm	71 x 83 x 70 mm
Manufacturer / Brand	...	DAHUA	DELTA	LEGRAND
Guarantee	2 years	3 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00