



	<a href="#">ACCESS POINT 4G+ LTE Cat. 6 +ROUTER ARCHER-MR500 Wi-Fi 2.4 GHz, 5 GHz, 300 Mbps + 867 Mbps TP-LINK</a>	<a href="#">POLE MOUNT BD-LP09</a>
		
	1368.28 NOK 1368.28 NOK	194.13 NOK 194.13 NOK
Suitable for cameras	...	OMEGA-21P22-6
Pole diameters range	...	Ø 90 ... Ø 120 mm
Material	...	Steel - powder painted
Color	...	White
Frequency range	<ul style="list-style-type: none"> <li>• Wi-Fi : 2.4 GHz, 5 GHz,</li> <li>• LTE : 2600 MHz, 2100 MHz, 1800 MHz, 800 MHz</li> </ul>	...
Antenna type	WiFi - built-in , 2 x 4G LTE - Omnidirectional antenna , SMA type connectors	...
Standards	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, 4G+ LTE, 3G HSPA+/HSPA/UMTS	...
Baud rates	<ul style="list-style-type: none"> <li>• Wi-Fi : 300 Mbps + 867 Mbps,</li> <li>• LTE Cat. 6 : 300 Mbps / 50 Mbps</li> </ul>	...
LAN ports	<ul style="list-style-type: none"> <li>• 1 x 10/100/1000 Mbps - LAN/WAN</li> <li>• 3 x 10/100/1000 Mbps - LAN</li> </ul>	...
Receiver sensitivity	5 GHz : <ul style="list-style-type: none"> <li>• 11a 54M : -77 dBm</li> <li>• 11ac HT20 : -73 dBm</li> <li>• 11ac HT40 : -68 dBm</li> <li>• 11ac HT80 : -64 dBm</li> <li>• 11n HT20 : -77 dBm</li> <li>• 11n HT40 : -73 dBm</li> </ul> 2.4 GHz : <ul style="list-style-type: none"> <li>• 11g 54M : -74 dBm</li> <li>• 11n HT20 : -72 dBm</li> <li>• 11n HT40 : -69 dBm</li> </ul>	...
Transmitter power	<ul style="list-style-type: none"> <li>• 5 GHz : &lt; 23 dBm</li> <li>• 2.4 GHz : &lt; 20 dBm</li> </ul>	...
LED indicators	Power, WAN, LTE, WLAN, LAN, Signal indicator	...

Network type	<ul style="list-style-type: none"> <li>• 4G : FDD-LTE B1/B3/B5/B7/B8/B20/B28 - 2100 / 1800 / 850 / 2600 / 900 / 800 / 700 MHz</li> <li>• 4G : TDD-LTE B38/B40/B41 - 2600 / 2300 / 2500 MHz</li> <li>• 3G : DC- HSPA+/HSPA/UMTS B1/B3/B5/B8 - 2100 / 850 / 900 MHz</li> </ul>	...
LTE	✓	...
QSS	—	...
WDS	—	...
DDNS	<ul style="list-style-type: none"> <li>• DynDNS</li> <li>• No-IP</li> <li>• TP-LINK</li> </ul>	...
DHCP server	✓	...
Firmware update	✓	...
Protections	<ul style="list-style-type: none"> <li>• WEP 64/128-bit, WPA/WPA2-Personal, WPA/WPA2-Enterprise</li> <li>• Support DoS defence</li> <li>• SPI network firewall</li> <li>• IP addresses filtering</li> <li>• IP-MAC Binding</li> </ul>	...
Management interface	Local, remote or via TP-Link Cloud management, Tether application	...
Operation modes	<ul style="list-style-type: none"> <li>• Router 4G LTE,</li> <li>• Router WiFi</li> </ul>	...

Main features	<ul style="list-style-type: none"> <li>• Plug &amp; Play - The nanoSIM cards support</li> <li>• MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network</li> <li>• Support for TP-Link OneMesh™ technology - max. 64 devices</li> <li>• IPTV compliance</li> <li>• Enable/disable wireless network</li> <li>• Wireless Network Schedule</li> <li>• WMM (Wi-Fi Multimedia)</li> <li>• Wireless transmission statistics</li> <li>• The failover function enabling automatic switching between 4G/WAN interface in the case of an Internet network connection loss</li> <li>• QoS - IP-layer bandwidth control mechanism</li> <li>• WAN : Static / dynamic routing, PPPoE, PPTP, L2TP</li> <li>• DHCP client/server support</li> <li>• Port forwarding : ALG, UPnP, DMZ</li> <li>• VPN Server: OpenVPN, PPTP VPN</li> <li>• URL addresses filtering</li> <li>• IPv6 compliance</li> <li>• Guest Network - a separate and secure network for guests</li> </ul>	...
Power supply	12 V DC / 1.5 A (power adapter included)	...
Operation temp	0 °C ... 40 °C	...
Permissible relative humidity	10 % ... 90 % (non-condensing)	...
Weight	0.378 kg	0.92 kg
Dimensions	202 x 141 x 34 mm	131 x 170 mm
Manufacturer / Brand	TP-LINK	...
Guarantee	3 years	2 years