




	BATTERY 12V/17AH- EUROPOWER-EP	IP SPEED DOME CAMERA OUTDOOR DS-2DE2A404IW- DE3(C0)(S6)(C) - 3.7 Mpx 2.8 ... 12 mm Hikvision	TV OR MONITOR MOUNT AX-MAGNUM	ACCESS POINT 4G+ LTE Cat. 6 +ROUTER ARCHER- MR500 Wi-Fi 2.4 GHz, 5 GHz, 300 Mbps + 867 Mbps TP-LINK	ELECTRIC CABLE YKY-5X10.0	FLUSH BOX 3-GANG PK-3X60/K-G/SG/EPN Elektro-Plast
						
	326.70 PLN 326.70 PLN	1455.00 PLN 1455.00 PLN	66.00 PLN 66.00 PLN	484.92 PLN 484.92 PLN	36.27 PLN 36.27 PLN	16.95 PLN 16.95 PLN
Standard	...	TCP/IP
Battery capacity	17 Ah
Number of sections	3
Mounting standard	VESA max. 600 x 400
Sensor	...	1/2.8 " Progressive Scan CMOS
Battery charging current	max. 5.1 A
In section	100 m . Price for 1m when buying a whole roll	...
Matrix size	...	3.7 Mpx
Battery type	Maintenance-free AGM (Absorbent Glass Mat) battery
Screen size range	32 " ... 65 "
Bearing capacity	30 kg
Connector	B1 / M5 screw
Distance from mounting surface	58 mm
Inner conductor	5 x 10.0 mm ² - Cu wire	...
Rated voltage	12 V	0.6 / 1 kV	...
Battery lifetime	6 ... 9 years
Material	Plastic
Tilt adjustment	-15 ° ... 5 °
Outer coating	Ø 18.5 mm - PVC	...
Frequency range	• Wi-Fi : 2.4 GHz, 5 GHz, • LTE : 2600 MHz, 2100 MHz, 1800 MHz, 800 MHz
Horizontal rotation	—
Coating color	Black	...
Rotation in the plane of the screen	—
Montage hole diameter	3 x Ø 67 mm
Resolution	...	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens	...	2.8 ... 12 mm
Antenna type	WiFi - built-in, 2 x 4G LTE - Omnidirectional antenna , SMA type connectors
View angle	...	97 ° ... 32 °
Optical zoom	...	x 4
Digital zoom	...	x 16
Range of IR illumination	...	20 m
Preset rotation speed	...	• 100 °/s (horizontal) • 100 °/s (vertical)
Standards	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, 4G+ LTE, 3G HSPA+/HSPA/UMTS
Rotation speed (manual control)	...	• 0.1 °/s ... 100 °/s (horizontal) • 0.1 °/s ... 100 °/s (vertical)
Horizontal rotation range	...	355 ° - Rotation of the head is limited by stops
Baud rates	• Wi-Fi : 300 Mbps + 867 Mbps, • LTE Cat. 6 : 300 Mbps / 50 Mbps
Vertical rotation range	...	0 ° ... 90 °
RS-485 interface	...	—
Number of presets	...	300
Horizontal scan	...	—
Route settings	...	—
LAN ports	• 1 x 10/100/1000 Mbps - LAN/WAN • 3 x 10/100/1000 Mbps - LAN
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	• Microphone built-in • External microphone input • Audio output • Bi-directional audio streaming support • Audio detection
Main stream frame rate	...	25 fps @ 3.7 Mpx
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Max. number of on-line users	...	20
ONVIF	...	✓
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default admin user / password	...	admin / - The administrator password should be set at the first start
Receiver sensitivity
Default IP address	...	192.168.1.64
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) -iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80
Transmitter power
RTSP URL	...	• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization
LED indicators	Power, WAN, LTE, WLAN, LAN, Signal indicator	...
Main features	...	• WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • SVC (Scalable Video Coding) - technology enabling the transfer of several sub-streams of different quality within one stream • NAS - Network Attached Storage support • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • ICR - Movable InfraRed filter • Privacy zones - max. 24 • Motion Detection • Sharpness - sharper image outlines • Image rotation and mirror • Intelligent image analysis : abandoned/missing object, crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, video tampering, face detection
Network type
LTE	✓	...
QSS	—	...
WDS	—	...
Power consumption	...	≤ 9.2 W @ 12 V DC
DDNS	• DynDNS • No-IP • TP-LINK	...
DHCP server	✓	...
Housing	...	Speed Dome, Metal
Firmware update	✓	...
Color	...	White + Black	Black	Yellow
"Index of Protection"	...	IP66	—
Vandal-proof	...	IK10
Operation temp	...	-20 °C ... 60 °C
Protections
Management interface	Local, remote or via TP-Link Cloud management, Tether application	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Operation modes	• Router 4G LTE, • Router WiFi
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Turkish, Hungarian, Italian
SAP Code	...	327000399
Main features	In the kit : Expansion plugs Ø 8 x 50 mm	<ul style="list-style-type: none"> • Plug & Play - The nanoSIM cards support • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Support for TP-Link OneMesh™ technology - max. 64 devices • IPTV compliance • Enable/disable wireless network • Wireless Network Schedule • WMM (Wi-Fi Multimedia) • Wireless transmission statistics • The failover function enabling automatic switching between 4G/WAN interface in the case of an Internet network connection loss • QoS - IP-layer bandwidth control mechanism • WAN : Static / dynamic routing, PPPoE, PPTP, L2TP • DHCP client/server support • Port forwarding : ALG, UPnP, DMZ • VPN Server: OpenVPN, PPTP-VPN • URL addresses filtering • IPv6 compliance • Guest Network - a separate and secure network for guests 	...	<ul style="list-style-type: none"> • Flush-mounted, for hollow walls • 4 special screws with holders to fastening to the wall - included
Power supply	...	• PoE (802.3af), • 12 V DC / 760 mA	...	12 V DC / 1.5 A (power adapter included)
Operation temp	0 °C ... 40 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)
Weight	6.1 kg	0.61 kg	1.27 kg	0.378 kg	75.6 kg @ 100 m	0.068 kg
Dimensions	181 x 77 x 167 mm	Ø 131 x 102 mm	640 x 420 x 50 mm	202 x 141 x 34 mm	...	3 x Ø 60 x 47 mm - Internal dimensions 211 x 72 x 48 mm - External dimensions
Manufacturer / Brand	...	Hikvision	...	TP-LINK	...	Elektro-Plast
Guarantee	2 years	3 years	2 years	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00