



	IP CAMERA GT-CI21C3-36 - 1080p 3.6 mm GEMINI TECHNOLOGY	DUAL SMART LIGHT TOUCH SWITCH ATLO-TB2- TUYA Wi-Fi, Tuya Smart
		
	87.45 EUR 87.45 EUR	10.18 EUR 10.18 EUR
Standard	TCP/IP	...
Sensor	1/2.8 " Sony CMOS IMX322	...
Application	...	Works with lighting - switching on/off
Digital Image Processor	Hisilicon 3516C	...
Matrix size	2.43 Mpx	...
Rated voltage	...	100 ... 240 V AC, 50 / 60 Hz
Maximum power	...	300 W (for each output)
Rated current	...	max. 10 A
Number of buttons	...	2 (touch)
Number of outputs	...	2
Connector type	...	screw terminals
Resolution	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p 960 x 540 - qHD 720 x 576 - D1	...
Wireless	...	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n
Lens	3.6 mm	...
Main features	...	<ul style="list-style-type: none"> • Local control by physical button, • schedule, • timer, • Setting scenarios by different events, • remote access, • voice control, • LED indication • Backlit, touch control panel • The product does not fit standard mounting boxes with a diameter of 60 mm
View angle	<ul style="list-style-type: none"> • 72 ° (manufacturer data) • 82 ° (our tests result) 	...
S/N ratio	> 50 dB	...
Operation temp	...	-20 °C ... 50 °C
Range of IR illumination	30 m	...

Permissible relative humidity	...	≤ 80 %
Image compression method	H.264, MJPEG	...
Alarm inputs / outputs	—	...
Bitrate	16 ... 8000 kbps	...
Main stream frame rate	max. 25 fps - 1080p	...
Network interface	10/100 Base-T (RJ-45)	...
Network protocols	TCP/IP, UDP, HTTP, DHCP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SNMP, ONVIF	...
Audio	—	...
Mobile phones support	Port no.: 5800 or access by a cloud (P2P) • Android: Free application Fseye • iOS: Free application Fseye	• The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Default admin user / password	admin / (null)	...
Default IP address	192.168.1.188	...
Web browser access ports	80, 554, 1935 - Firmware V1.0, V1.1 80, 5050, 5051, 5052 - Firmware V4.0 - V4.3	...
PC client access ports	5050, 5051, 5052	...
WEB Server	Built-in	...
Mobile client access ports	5800	...
Port ONVIF	80 - Firmware V1.0, V1.1 8000 - Firmware V4.0 - V4.3	...
RTSP URL	rtsp://ip_address:554/ch01.264 - Main stream rtsp://ip_address:554/ch01_sub.264 - Sub stream	...
ONVIF	2.21	...
Max. number of on-line users	10 10	...
RS-485 interface	—	...

Main features	<ul style="list-style-type: none"> • ICR - Movable InfraRed filter • 3D-DNR - Digital Noise Reduction • WDR - Wide Dynamic Range • Possibility to change the resolution, quality and bit rate • Additional "Spot" CVBS output - allows to quick view the image from camera and its configuration without the need to disconnect it from monitoring system • Time mark and image description • Image rotation and mirror • Configurable: brightness, contrast, saturation • Sharpness - sharper image outlines • Day/Night mode - configurable • Possibility to add different privileges to the users • Privacy zones - max. 4 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 420 mA 	...
Power consumption	max. 4.7 W	...
Housing	Metal	Plastic + Acrylic glass (plexiglass)
Color	Dark graphite	White
"Index of Protection"	IP67	...
Operation temp	-20 °C ... 55 °C	...
Weight	0.496 kg	0.134 kg
Dimensions	192 x 102 x 69 mm	86 x 86 x 34 mm
Supported languages	English, Polish	...
Manufacturer / Brand	GEMINI TECHNOLOGY	...
Guarantee	2 years	2 years