

	ANGULAR PLUG LE-50184 230 V 16 A LEGRAND	ANGULAR PLUG LE-50183 230 V 16 A LEGRAND	CONVERTER IPM- AE7-0020A DAHUA	SET OF UTP / 2-WIRE CONVERTERS FOR LAN+POE TRANSMISSION ETH10-2WIRE-SET 2 PCS SET ATTE
				
	3.58 EUR 3.58 EUR	3.58 EUR 3.58 EUR	116.22 EUR 116.22 EUR	88.24 EUR 88.24 EUR
Compatibility	Dahua ANPR cameras	...
Rated voltage	230 V / 50 Hz	230 V / 50 Hz
Input	RS-485 interface	...
Maximal current load	16 A	16 A
Grounding	—	—
Output	Wiegand interface - 26 bit	...
Electrical cable	max. 2 x 1.5 mm ²	max. 2 x 1.5 mm ²
Cable terminals	screw terminals	screw terminals
Plug type	CEE 7/17	CEE 7/17
Connectors	<ul style="list-style-type: none"> • 1 pcs RJ45 • 1 pcs terminals (screw terminals) - 0.32 ... 3.3 mm² (22 ... 12 AWG)
LAN ports	1 pcs RJ45 10 Mbps
Color	Black	White
Connectors description	<p>ETH10-2WIRE-TX :</p> <ul style="list-style-type: none"> • PoE IN - Passive PoE ≤ 30 W, PoE (802.3at) ≤ 30 W, PoE (802.3af) ≤ 15 W ("+" : 1, 2 pins; "-" : 3, 6 pins) or ("+" : 4, 5 pins; "-" : 7, 8 pins) • Power • DATA - 2-wire <p>ETH10-2WIRE-RX :</p> <ul style="list-style-type: none"> • PoE OUT - Passive PoE ("+" : 4, 5 pins; "-" : 7, 8 pins) • Power • DATA - 2-wire
Transmission speed	10 Mbps
Transmission range	<ul style="list-style-type: none"> • 1000 m @ 2-wire • 100 m @ UTP : Switch PoE - ETH10-2WIRE-TX • 100 m @ UTP : ETH10-2WIRE-RX - IP Camera
LED indicators	<ul style="list-style-type: none"> • Power • LAN • 2-wire
Protections	<ul style="list-style-type: none"> • Overvoltage - LAN, DATA • Protection against reverse polarity connection - Power • Overload 0.6 A - PoE IN ETH10-2WIRE-TX

Main features	<ul style="list-style-type: none"> • Plug & Play • Support for IP cameras and network devices • Full transparency for networks • Operation modes - Set with jumpers
Power supply	12 V DC / 20 mA (power adapter not included)	ETH10-2WIRE-TX : <ul style="list-style-type: none"> • 30 ... 56 V DC - PoE • 10 ... 56 V DC - Power ETH10-2WIRE-RX : <ul style="list-style-type: none"> • 10 ... 56 V - Power • The output PoE voltage is equal to the input voltage
Power consumption	1.35 W (total)
Housing	Plastic (PC)
"Index of Protection"	IP20
Operation temp	-25 °C ... 65 °C
Weight	0.022 kg	0.022 kg	0.16 kg	0.03 kg (single element)
Dimensions	Ø 37 x 49 mm	Ø 37 x 49 mm	99 x 72 x 17 mm	51 x 51 x 24 mm (single element)
Manufacturer / Brand	LEGRAND	LEGRAND	DAHUA	ATTE
Guarantee	2 years	2 years	3 years	3 years